

Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 25-2324-9 **Version Number:** 2.06 10/23/14 08/19/14 **Issue Date: Supercedes Date:**

SECTION 1: Identification

1.1. Product identifier

3MTM Abrasive Products, TrizactTM 464LA, 468LA

1.2. Recommended use and restrictions on use

Recommended use

Abrasive Product

1.3. Supplier's details

MANUFACTURER:

DIVISION: Abrasive Systems Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable.

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
HIPTEUICH	C.A.D. INU.	1 /O DV VVL

3MTM Abrasive Products, TrizactTM 464LA, 468LA 10/23/14

Silicon Carbide Mineral	409-21-2	10 - 30
Synthetic Amorphous Silica, Fumed, Crystalline Free	112945-52-5	0.1 - 2.5
Additive	84133-50-6	0.01 - 2
Lubricant	8042-47-5	0 - 0.2
Cured Resin	Mixture	10 - 30
Film Backing	Mixture	50 - 70

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eve Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

No need for first aid is anticipated.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Observe precautions from other sections.

6.2. Environmental precautions

Not applicable.

Page 2 of 9

6.3. Methods and material for containment and cleaning up

Not applicable.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of dust created by sanding, grinding or machining. Combustible dust may form by action of this product on another material (substrate). Dust generated from the substrate during use of this product may be explosive if in sufficient concentration with an ignition source. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
SILICA, AMORPHOUS	112945-52-	OSHA	TWA concentration:0.8	
	5		mg/m3;TWA:20 millions of	
			particles/cu. ft.	
Silicon Carbide Mineral	409-21-2	OSHA	TWA(as total dust):15	
			mg/m3;TWA(respirable	
			fraction):5 mg/m3	
Lubricant	8042-47-5	CMRG	TWA:5 mg/m3;STEL:10	
			mg/m3	
MINERAL OILS, HIGHLY-	8042-47-5	ACGIH	TWA(inhalable fraction):5	A4: Not class. as human
REFINED OILS			mg/m3	carcin
Paraffin oil	8042-47-5	OSHA	TWA(as mist):5 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Provide local exhaust at process emission sources to control exposure near the source and to prevent the escape of dust into the work area. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

8.2.2. Personal protective equipment (PPE)

Eye/face protection

3MTM Abrasive Products, TrizactTM 464LA, 468LA 10/23/14

To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection

Wear appropriate gloves to minimize risk of injury to skin from contact with dust or physical abrasion from grinding or sanding.

Respiratory protection

Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:

Odor, Color, Grade: Solid Abrasive Product

Odor threshold Not Applicable Not Applicable рH Not Applicable **Melting point Boiling Point** Not Applicable Flash Point Not Applicable Not Applicable **Evaporation rate** Not Classified Flammability (solid, gas) Flammable Limits(LEL) Not Applicable Not Applicable Flammable Limits(UEL) Not Applicable Vapor Pressure **Vapor Density** Not Applicable **Specific Gravity** Not Applicable Solubility in Water Not Applicable Not Applicable Solubility- non-water Partition coefficient: n-octanol/ water Not Applicable **Autoignition temperature** Not Applicable Not Applicable **Decomposition temperature** Not Applicable Viscosity

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

3MTM Abrasive Products, TrizactTM 464LA, 468LA 10/23/14

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Dust from grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Allergic Skin Reaction (non-photo induced) in sensitive people: Signs/symptoms may include redness, swelling, blistering, and itching.

Eve Contact:

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

No health effects are expected.

Additional Information:

This product, when used under reasonable conditions and in accordance with the 3M directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards.

This document covers only the 3M product. For complete assessment, when determining the degree of hazard, the material being abraded must also be considered.

Page 5 of 9

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Silicon Carbide Mineral	Dermal	Rat	LD50 > 2,000 mg/kg
Silicon Carbide Mineral	Ingestion	Rat	LD50 > 2,000 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Rat	LD50 > 5,110 mg/kg
Additive	Dermal	Rabbit	LD50 1,127 mg/kg
Additive	Inhalation- Dust/Mist (4 hours)	Rat	LC50 1.1 mg/l
Additive	Ingestion	Rat	LD50 412 mg/kg
Lubricant	Dermal	Rabbit	LD50 > 2,000 mg/kg
Lubricant	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Silicon Carbide Mineral	Rat	No significant irritation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation
Lubricant	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Silicon Carbide Mineral	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation
Lubricant	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	Human	Not sensitizing
	and	
	animal	
Lubricant	Guinea	Not sensitizing
	pig	

Respiratory Sensitization

Name	Species	Value

Germ Cell Mutagenicity

Name	Route	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	In Vitro	Not mutagenic
Lubricant	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification
Lubricant	Dermal	Mouse	Not carcinogenic
Lubricant	Inhalation	Multiple	Not carcinogenic
		animal	
		species	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
Lubricant	Ingestion	Not toxic to female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Lubricant	Ingestion	Not toxic to male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Lubricant	Ingestion	Not toxic to development	Rat	NOAEL 4,350 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

		I				
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
						Duration

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
						Duration
Synthetic Amorphous	Inhalation	respiratory system	All data are negative	Human	NOAEL Not	occupational
Silica, Fumed, Crystalline		silicosis			available	exposure
Free						
Lubricant	Ingestion	hematopoietic	Some positive data exist, but the	Rat	NOAEL	90 days
		system	data are not sufficient for		1,381	-
			classification		mg/kg/day	
Lubricant	Ingestion	liver immune	Some positive data exist, but the	Rat	NOAEL	90 days
	_	system	data are not sufficient for		1,336	-
			classification		mg/kg/day	

Aspiration Hazard

Name	Value
Lubricant	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. The substrate that was abraded must be considered as a factor in the disposal method for this product. Dispose of waste product in a permitted industrial waste facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 0 Flammability: 0 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar

3MTM Abrasive Products, TrizactTM 464LA, 468LA 10/23/14

emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 25-2324-9
 Version Number:
 2.06

 Issue Date:
 10/23/14
 Supercedes Date:
 08/19/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Page 9 of 9