

### STAINLESS STEEL

## Ice Bin & Drainboard Combo Units 🔞 **21" Wide**





# Item #: \_\_\_\_\_ Qty #: \_\_\_\_ Model #: \_\_ Project #: \_



Optional Sliding Stainless Steel Cover Shown

#### **FEATURES:**

4" backsplash.

8" deep insulated ice bin.

Two removable injection molded 3-pack plastic bottle racks.

24" seamless & embossed drainboard.

Galvanized legs with adjustable plastic bullet feet.

Adjustable galvanized side cross-bracing.

Includes rear deck for extra storage.

#### **MECHANICAL:**

1" IPS drain (drainboard and non-cold plate ice bin) 1/2" IPS drain (cold-plate bin)

**Bottle Racks Must Be Removed For NSF Compliance** And For Use With Optional Cover.

#### **MATERIAL:**

Ice Bin, Front Apron, Backsplash: 22 gauge, 300 stainless steel

Sides: 20 gauge, 430 stainless steel

Understructure: 22 gauge galvaneal front/back;

11 gauge electrogalvaneal leg channel

Legs: 1 5/8" O.D. 18 gauge, galvanized steel with

adjustable plastic bullet feet

Ice Bin Insulation: 2 lbs. density styrofoam (non-cold plate models); 2

lbs. density foam-in-place (cold-plate models)

**Cold Plate:** Cast aluminum with 7 circuits (5 syrup and 2 water lines)

with 5/16" diameter stainless steel bump and swedge ends

#### **OPTIONAL:**

SU-10A - 18" stainless steel leg upgrade

**SU-13 -** 10-circuit cold plate upgrade (For -7 models only)

SU-30 - Soda chase provision

SU-40 - Prep unit for installation of speed rail

SU-61 - Special sizing

SU-68 - Omit corrugation on drainboard

SSC-24 - Sliding cover for 24" ice bin

21" WIDE Model #	Overall Length	Ice Bin Capacity	Ice Bin Location	Approx. Weight	Approx. Cu. Ft.
CRW-4L	48"	35 lbs.	Left	72 lbs.	13
CRW-4R	48"	35 lbs.	Right	72 lbs.	13

#### With 7-Circuit Cold Plate

CRW-4L-7	48"	35 lbs.	Left	108 lbs.	13
CRW-4R-7	48"	35 lbs.	Right	108 lbs.	13



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

## **DIMENSIONS and SPECIFICATIONS**

TOL Overall: ± .500" Interior: ± .250"

ALL DIMENSIONS ARE TYPICAL



