

Safety Data Sheet Resinoid Bonded Cutting Off and Grinding Wheels (Metal)

StanleyBlack&Decker

1. Identification			
Product identifier	Resinoid Bonded Cutting Off and Grinding Wheels (Metal)		
Product code	N.Av.		
Other means of identification	None.		
Recommended use of the chemical and restrictions on use	Use for abrasive or cut work with ferrous metal.		
Manufacturer	Stanley Black & Decker Canada Corp. 6935 Picard Street St-Hyacinthe, QC Canada J2S 1H3 Tel. 450-774-4660 www.stanleyblackanddecker.com		
Emergency phone number	450-774-4660		

2. Hazard identification

Avoid breathing dust. Avoid contact with eyes. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved.

WHMIS 2015/OSHA HCS 2012/GHS

Not Regulated under WHMIS 2015/GHS

P261: Avoid breathing dust.

P264: Wash skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves, protective clothing and eye protection.

P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to

do. Continue rinsing.

3. Composition/information on ingredients			
Common name	CAS	Weight % content	
Aluminum oxide	1344-28-1	60 - 83 %	
Fiberglass discs	Fiber-1	15 - 25 %	
Cured Phenolic resin	Resin-1	8 - 17 %	
Barium sulfate	7727-43-7	0 - 11 %	
Furfural	98-01-1	0 - 1 %	
Iron disulfide	12068-85-8	0 - 20 %	
Aluminum potassium fluoride	60304-36-1	0 - 8 %	

Note: The Cured Phenolic resin is an ingredient of unknown toxicity. However, according to its chemical family, no adverse effect is expected under normal conditions of use. Fiberglass discs is an ingredient of unknown toxicity. However, according to its chemical family, no adverse effect is expected under normal conditions of use.

4. First-aid measures		
Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.	
Skin contact	Wash skin with warm water and mild soap. Remove contaminated clothing and wash before reuse. If a problem develops or persists, seek medical attention.	
Eye contact	IMMEDIATELY flush with plenty of water. Flush with water for at least 15 minutes. Remove contact lenses. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.	
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If ingestion of a large amount does occur, seek medical attention or contact a Poison Centre immediately.	
Other	Grinding may create elevated sound levels (during grinding) which may affect hearing and pre-existing hearing condition(s). If a problem develops or persists, seek medical attention.	
Symptoms	Dust may irritate throat and respiratory system and cause coughing. Dusts from this product may cause mechanical irritation to skin and eyes.	
Notes to the physician	Treat symptomatically.	

5. Fire-fighting measures		
Suitable extinguishing media	Use appropriate extinguisher for surrounding fire.	
Specific hazards arising from the chemical	No hazard listed.	
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask.	
Special protective actions for fire-fighters	No additional information.	

6. Accidental release measures			
Personal precautions, protective equipment and emergency procedures	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.		
Environmental precautions	DO NOT throw dust into drains or waterways.		
Methods and materials for containment and cleaning up	Ventilate the area well. Vacuum or sweep up dust and place in an appropriate waste disposal container. Avoid generating dusty conditions.		

7. Handling and storage		
Precautions for safe handling	Handle abrasive cutting off wheels and grinding wheels carefully to prevent damage from shock, heat, etc. Use all abrasive cutting off wheels and grinding wheels in accordance with all applicable federal and state safety codes and as directed in ANSI B7.1: Safety Requirements for the Use, Care, and Protection of Abrasive Wheels. Also consult ANSI B.1: Safety Requirements for the Use, Care, and Protection of Abrasive Wheels. Use only in well ventilated area. Avoid breathing dust. Use in a maner that avoids generating dust. Avoid contact with eyes. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound. Remove contaminated clothing and wash before reuse.	
Conditions for safe storage, including any incompatibilities	Store in dry protected area free from humidity, freezing temperatures or extreme temperature changes.	
Storage temperature	5 to 45°C (41 to 113°F)	

8. Exposure con	trols/persona	al protection			
Immediately Dangerous to Life or Health	Fulfural: 100 ppm. Barium sulfate: 1000 mg/m3, value as Ba (Barium). Aluminum potassium fluoride: 250 mg/m3, value as F (fluoride).				
Aluminum oxide	TWA (8h)	Respirable Dust		1 mg/m ³	ACGIH , BC
		Total Dust		10 mg/m ³	ON , RSST
Fiberglass discs	TWA (8h)	Respirable Dust		3 mg/m ³	ACGIH
		Total Dust		10 mg/m ³	ACGIH , RSST
Cured Phenolic resin	TWA (8h)	Respirable Dust		3 mg/m ³	ACGIH
		Total Dust		10 mg/m ³	ACGIH
Barium sulfate	TWA (8h)	Respirable Dust		3 mg/m ³	BC
		Inhalable Fraction		5 mg/m ³	ACGIH, BC, RSST
		Total Dust		10 mg/m ³	ON, RSST
Aluminum potassium fluo	` '		_	2.5 mg/m ³	ACGIH, BC, ON, RSST
Furfural	TWA (8h)		2 ppm	7 0 / 0	ACGIH, BC, ON
			2 ppm	7.9 mg/m ³	RSST (Pc)
Appropriate engineering controls	Provide sufficient mechanical (general and/or local exhaust) to keep the airborn concentrations of dust below their respective occupational exposure limits. It is recommended to reduce the sound level in order not to exceed the standards OSHA 29CFR 1910.95, ANSI S3.19 and/or CSA Z94.2 (Canada) for hearing protection devices. In addition, the hearing protection devices must be selected based to the sound spectrum emitted in the workplace.				
Individual protection me	easures				
Eye	Wear safety glasse	es. If risk of contact wi	th eyes or t	the face, wear a f	ace shield.
Hands	Wear leather gloves.				
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. If necessary, wear an apron or long-sleeve protective coverall suit.				
Respiratory	A respirator is not required in a well-ventilated area. Where the conditions in the workplace require a respirator, it is necessary to follow a respiratory protection program. Moreover, respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and standard 29 CFR 1910.134 (OSHA), ANSI Z88.2 or CSA Z 94.11 (Canada) and approved by NIOSH/MSHA. For nuisance exposures use type N95 particle respirator.				
Feet	Wear safety shoes.				



Physical state	Solid wheel	Flammability	Non-flammable.
Colour	Black, dark brown or reddish	Flammability limits	N/Ap.
Odour	Slight odor	Flash point N/Ap.	
Odour threshold	N/Av. Auto-ignition N/Av. temperature		N/Av.
рН	N/Ap. Sensibility to electrostatic charges		No
Melting point	N/Av.	N/Av. Sensibility to sparks and/or friction	
Freezing point	N/Ap.	Vapour density	N/Av. (Air = 1)
Boiling point	N/Ap.	Relative density Variable (V	
Solubility	Negligible in water	Partition coefficient n-octanol/water	N/Ap.
Evaporation rate	N/Ap.	Decomposition temperature	N/Av.
Vapour pressure	N/Ap.	Viscosity	N/Ap.
Percent Volatile	0%	Molecular mass	N/Ap.

10. Stability and reactivity			
Reactivity	Contact with acid liberates a toxic gas.		
Chemical stability	Stable under normal conditions of use.		
Possibility of hazardous reactions (including polymerizations)	Hazardous polymerization will not occur under recommended storage.		
Conditions to avoid	Avoid contact with incompatible materials.		
Incompatible materials	Strong acids.		
Hazardous decomposition products	In use, the grinding wheel will generate dust and odors. In most cases, the material removed from the work piece will be significantly greater than that generated from the grinding wheel. Coolants, if used, may produce other decomposition products.		

11. Toxicolo	ogical informati	ion			
Numerical measures of toxicity	Aluminum oxide	Ingestion >5000 mg/kg Rat LD50 Inhalation >2.6 mg/l/4h Rat LC50 Skin >2000 mg/kg Rabbit LD50			
	Aluminum potassium	fluoride Ingestion 2720 mg/kg Rat LD50			
		Inhalation >4.9 mg/l/1h Rat LC50 Skin >2000 mg/kg Rabbit LD50			
	Furfural	Ingestion 127 mg/kg Rat LD50			
		Inhalation >0.54 mg/l/4h Rat LC50			
		<1.63 mg/l/4h Rat LC50			
	Barium sulfate	Skin <1000 mg/kg Rabbit LD50 Ingestion >3000 mg/kg Mouse LD50			
	Dariam Sanate	Skin >2000 mg/kg Rabbit LD50			
Likely routes of exposure	Skin, eyes, inhalation				
Delayed,	Eye contact	Exposure to dust may cause redness and irritation to eyes.			
immediate and chronic effects	Skin contact	Exposure to dust may cause redness and irritation of the skin.			
chronic effects	Dust may irritate throat and respiratory system and cause coughing. Reprolonged occupational overexposure to dusts may cause lung damage				
	Ingestion	Not a likely route of exposure. Exposure to dust may cause gastrointestinal irritation.			
	Respiratory or skin sensitization	Ingredients present at levels greater than or equal to 0.1% of this product are not skin or respiratory sensitizers.			
	IARC/NTP	No ingredients listed.			
	Classification				
	Carcinogenicity	Furfural is a confirmed animal carcinogen with unknown relevance to humans (ACGIH). Moreover, it is not classifiable as to its carcinogenicity to humans (IARC, Group 3).			
	Mutagenicity	Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause mutagenic effects.			
	Reproductive toxicity	Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause reproduction effects.			
	Specific target organ toxicity - single exposure	Respiratory system.			
	Specific target organ toxicity - repeated exposure	No target organ is listed.			
Interactive effects	No information available for this product.				
Other information	No additional informa	tion.			

12. Ecological information		
Ecological toxicity	Fish LC50 N.Av.	
Persistence	May persist in the environment.	
Degradability	This product is not biodegradable.	
Bioaccumulative potential	No bioaccumulation.	
Mobility in soil	The product has no mobility in the soil. However, some ingredients (listed fluorides) are slightly soluble in	

	water and have moderate mobility in wet soil.
Other adverse effects	This chemical does not deplete the ozone layer.

13. Disposal considerations

Container

Important! Prevent waste generation. Use in full. Waste product may be send to landfill. Empty containers can be treated (recycled) wherever there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.

14. Transport inf	ormation					
UN Number	UN					
UN Proper Shipping Name	Not regulated by TDG (Canada) and 49 CFR DOT (USA).					
Environmental hazards	This material is not listed as a marine pollutant.					
Special precautions for user	No information available for this product.					
TDG - Transportation of	Dangerous Goods (Canada)					
Transport hazard class(es)	Not regulated					
Packing group	Not regulated					
Emergency response guidebook 2012						
IMO/IMDG - Internationa	Maritime Transport					
Classification	Not regulated					
IATA - International Air	Transport Association					
Classification	Not regulated					
	are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper					

15. Regulatory information

CANADA

Common name	CAS	CEPA	DSL	NDSL	NPRI
Aluminum oxide	1344-28-1		X		X
Fiberglass discs	Fiber-1				
Cured Phenolic resin	Resin-1				
Barium sulfate	7727-43-7		Х		
Furfural	98-01-1		X		
Iron disulfide	12068-85-8			Х	
Aluminum potassium fluoride	60304-36-1		Х		

transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act
- DSL: Domestic Substances List Inventory
- NDSL: Non-Domestic Substances List Inventory

- NPRI: National Pollutant Release Inventory Substances

UNITED STATE OF AMERICA

Common name	CAS	TSCA	CER CLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Prio.
Aluminum oxide	1344-28-1	Х		X						
Fiberglass discs	Fiber-1									
Cured Phenolic resin	Resin-1									
Barium sulfate	7727-43-7	Х		X						
Furfural	98-01-1	X	X						Χ	
Iron disulfide	12068-85-8	X								
Aluminum potassium fluoride	60304-36-1	Х								

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act Hazardous Organic National Emission Standard for Hazardous Air Pollutant
- CAA 112(b) HAP: Clean Air Act Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act Regulated Chemicals for Accidental Release Prevention
- CWA 311: Clean Water Act List of Hazardous Substances
- CWA Priority: Clean Water Act Priority Pollutant list

California Proposition 65

No ingredients listed.

Other regulations

WHMIS 1988



Non-WHMIS controlled









16. Other information					
Date (YYYY-MM-DD)	Stanley Black & Decker Canada Corp. 2016-05-17				
Version	01				
Other information	REFERENCES: - Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, http://hazmap.nlm.nih.gov/index.php - TOXNET Databases, Toxicology Data Network, NIH U.S. National Library of Medicine, http://toxnet.nlm.nih.gov/ - Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), http://www.reptox.csst.qc.ca				

- OECD Existing Chemicals Database, Chemicals Screening Information DataSet (SIDS) for High Volume Chemicals, UNEP publications, http://webnet.oecd.org/HPV/UI/Search.aspx

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

OSHA: Occupational Safety and Health Administration (USA) NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

RSST: Règlement sur la santé et la sécurité du travail (Québec)

GHS: Globally Harmonized System

IARC: International Agency for Research on Cancer IDLH: Immediately Dangerous to Life or Health STEL: Short Term Exposure Limit (15 min)

TWA: Time Weighted Averages

WHMIS: Workplace Hazardous Materials Information System

To the best of our knowledge, the information contained herein is accurate. However, neither Préventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.