

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

YEAR PARTS & LABOR

WARRANTY

Solid Door Refrigerator

Reach-In Top Mount

M3 Series

Model: M3R24-1

___ FEATURES & BENEFITS =__

■ Digital temperature control system

Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.

■ High-tech monitor

The monitor digitally displays the present temperature. You can easily change the temperature by adjusting the digital temperature controller.

Hot gas condensate system

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

■ Reversible door hinge

LED interior lighting system

Brighter and longer lasting LED lights provide attractive, enhanced illumination compared to fluorescents. It saves energy by producing less heat, while maximizing the visibility.

■ Door pressure release device

Pressure relief doors are designed to eliminates vacuum pressure and allows easy, instant door opening.

■ Efficient refrigeration system

M3's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

Stainless steel cabinet construction

The Turbo Air M3 refrigerator model boasts a stainless steel exterior (galvanized steel top, bottom and back) and stainless steel interior with AL inside walls and door liners. It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury. The M3 can add a touch of style to the most refined setting.

Automatic evaporator fan motor delays

When the door is opened the evaporator fan will stop, preventing the circulation of hot and moist air from escaping into the refrigerator. This increases energy efficiency and lengthens the life of the compressor.

Adjustable, heavy duty, PE(polyethylene) coated wire shelves

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.



Refrigerator holds 33°F ~ 38°F for the best in food preservation











ENERGY STAR® Qualified

Model	Swing Door	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H † (inches)
M3R24-1	1	24	3	1/4	5.5	270	283/4 x 303/4 x 78

(unit: inch)

Solid Door Refrigerator

Model: M3R24-1

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type					
Full Load Amperes	5.5				
Compressor HP	1/4				
Feed Wires with Ground	3				
Cord Length (ft.)	9				
Refrigerant	R-134A				
DIMENSIONAL DATA					
# of Doors	1				
# of Racks Accepted	1				
Net Capacity (cu. ft.)	24				
Ext. Length Overall (in.)	283/4 (730mm)				
Ext. Depth Overall (in.)*	303/4 (780mm)				
Ext. Height Overall (in.)†	78 (1981mm)				
Int. Length Overall (in.)	243/4 (629mm)				
Int. Depth Overall (in.)	261/2 (675mm)				
Int. Height Overall (in.)	605/8 (1539mm)				
Gross Weight (lbs.)	270				
# of Shelves	3				
Shelf Size (L x D) (in.)	231/2 x 233/4				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 2" for rear condensate enclosure.

† Height does not include 5" for caster height.

■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Door locks standard
- Solid and sturdy grille design

OPTIONAL ACCESSORIES :


- ☐ 5" diameter swivel casters
- 6" height stainless steel legs
- Additional PE coated wire shelves
- ☐ Half door bun tray racks.


Each holds up to seven 18"L x 26"D sheet pans (sold separately)

☐ Full door bun tray racks.

Each holds up to fifteen 18"L x 26"D sheet pans (sold separately)

PLAN VIEW





Ver.201509











ENERGY STAR® Qualified

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002









