

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project :       |      |  |
|-----------------|------|--|
| Model #:        |      |  |
| Item #:         | Qty: |  |
| Available W/H : |      |  |
| Approval :      |      |  |

# Sandwich / Salad Unit

Food Prep Tables - Sandwich/Salad Prep Super Deluxe Series

**Model: TST-72SD** 

3 YEAR PARTS & LABOR WARRANTY



#### == FEATURES & BENEFITS ==\_

#### Cold air compartment

Our innovative "Cold air compartment" maintains temperature evenly for each pan to preserve fresh food longer. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

#### Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe can add a touch of style to the most refined setting.

#### Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

#### Convenient cutting board side rail

Our cutting board is 9-1/2" deep and 1/2" thick to provide ample working space, and is made of easy to use and sanitize LDPE (Low Density Polyethylene). The new side rail cutting board bracket makes it easy to secure and remove the cutting board and it accepts different sizes too (max. 1/2" thickness)

#### Hot gas condensate system

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

### Insulated pan cover

#### ■ Efficient refrigeration system

Turbo Air's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

#### High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place high density, CFC free polyurethane insulation.

#### ■ Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

#### Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

## Refrigerator holds 33°F ~ 39°F for the best in food preservation









| Model    | Swing<br>Door | CU./FT. | #of<br>Shelves | #of<br>Pans | HP  | AMPS | Crated<br>Weight (lbs.) | L x D*x H† (inches) |
|----------|---------------|---------|----------------|-------------|-----|------|-------------------------|---------------------|
| TST-72SD | 3             | 19      | 3              | 18          | 1/2 | 9.9  | 372                     | 725/8 x 30 x 37     |

# Sandwich / Salad Unit

## Model: TST-72SD

| ELECTRICAL DATA            |                |  |  |  |  |
|----------------------------|----------------|--|--|--|--|
| Voltage                    | 115/60/1       |  |  |  |  |
| Plug Type                  |                |  |  |  |  |
| Full Load Amperes          | 9.9            |  |  |  |  |
| Compressor HP              | 1/2            |  |  |  |  |
| Feed Wires with Ground     | 3              |  |  |  |  |
| Cord Length (ft.)          | 9              |  |  |  |  |
| Refrigerant                | R-134A         |  |  |  |  |
| DIMENSIONAL DATA           |                |  |  |  |  |
| Ext. Length Overall (in.)  | 725/8 (1846mm) |  |  |  |  |
| Ext. Depth Overall (in.)*  | 30 (762mm)     |  |  |  |  |
| Ext. Height Overall (in.)† | 37 (940mm)     |  |  |  |  |
| # of Doors                 | 3              |  |  |  |  |
| # of Shelves               | 3              |  |  |  |  |
| # of Pans                  | 18             |  |  |  |  |
| # of Hood                  | 2              |  |  |  |  |
| Net Capacity (cu. ft.)     | 19             |  |  |  |  |
| Net Weight (lbs.)          | 344            |  |  |  |  |
| Gross Weight (lbs.)        | 372            |  |  |  |  |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

\* Depth does not include 1" for rear spacers. † Height does not include 5" for caster height.


# 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Standard 1/6 size, 4" deep condiment pans included
- 91/2" deep, 1/2" thick cutting board included


#### ■ OPTIONAL ACCESSORIES:

- ☐ 2.5" dia. casters available ½" diameter & 13 TPI
- □ 5" diameter casters
- ☐ 6" height ABS plastic legs
- □ Additional stainless steel shelves
- ☐ Stainless steel double overshelf available
- ☐ Door locks available (extra lead time will apply)
- ☐ External digital thermometer available (extra lead time will apply)
- ☐ Removable food covers available

**PLAN VIEW** (unit: inch)



**PLAN VIEW** 



SIDE VIEW

Ver 201509














■ Warranty: 800-381-7770 ■ AC: 888-900-1002









