

SUPERBAY WA22 SERIES

22" ACRYLIC REFLECTOR

Cat. #		Approvals
Job	Type	



APPLICATIONS


- Designed as the economical solution to all non-impact applications. Clear lighting grade acrylic allows about 20% uplight for a well-lit application.

SPECIFICATIONS

- Lightweight prismatic acrylic reflector generates wide, uniform light distribution with minimum glare and reduces harsh shadows on vertical work surfaces.
- Acrylic composition of the reflector versus glass enhances work place safety. Injection molded of UV stabilized acrylic.
- Field-adjustable reflector brackets allow for medium to wide lighting distributions. Unit Pack Available! #BL-400P8-WA-WH-UPL
- Use coated (diffuse) lamps for optimum photometric performance.

LISTINGS


- Up to 55°C ambient. Suitable for damp location, minimum 90°C supply conductors.



	A	B	C	D	E	F
Flush Mount						
SLICK-ON®	23 1/2"	22 1/2"	9 1/2"	14"	9 1/2"	2"
	597 mm	572 mm	241 mm	356 mm	241 mm	51 mm
QUICK-ON®	22 5/8"	22 1/2"	8 5/8"	14"	9 1/2"	1 1/8"
	575 mm	572 mm	219 mm	356 mm	241 mm	29 mm
Leg Mount						
SLICK-ON®	25 3/4"-28"	22 1/2"	9 1/2"	14"	9 1/2"	2"
	654-711 mm	572 mm	241 mm	356 mm	241 mm	51 mm
QUICK-ON®	24 7/8"-27 1/8"	22 1/2"	8 5/8"	14"	9 1/2"	1 1/8"
	632-689 mm	572 mm	219 mm	356 mm	241 mm	29 mm

ORDERING INFORMATION

ORDERING EXAMPLE: BL-350P8-WA22-WH



SERIES

BL Superbay Series

SOURCE

S High Pressure Sodium
P Pulse Start Metal Halide

OPTICS

WA22 22" Wide Acrylic Reflector

SOCKET

EX Exclusionary socket
Required for PSMH

WATTAGE

175 175 watt only Pulse Start MH only
250 250 watt Pulse Start MH or HPS
320 320 watt Pulse Start MH only
400 400 watt Pulse Start MH or HPS

VOLTAGE

5 480V
8 Quad-Tap® - 120/208/240/277V

COLOR

WH White (standard)
GR Gray (optional)

MAX AMBIENT TEMPERATURE

WATTAGE	OPEN	ENCLOSED
250	55°C	55°C
320	55°C	55°C
400	55°C	55°C

ACCESSORIES

Order separately

NOTE: Energy Saving Linear Reactor Pulse Start ballast available, consult factory (277V only).

NOTE: Bottom enclosures are required unless lamps designated as "suitable for open use" are used.

NOTE: Options must be added as suffix to Catalog Number. Accessories must be ordered separately.

BOTTOM ENCLOSURES

WA2-ENC Bottom Enclosure
WA22-CDL Conical Bottom Enclosure
WA22-DLR Drop Lens Bottom Enclosure

WA UNIT PACKS

MATERIAL	MATERIAL DESCRIPTION	WATTAGE	VOLTAGE	LAMP BASE	LAMP INCLUDED
METAL HALIDE PULSE START					
BL400P8WAWHUPL	BL-400P8-WA-WH-UPL	400	Quad-Tap	Exclusionary	Lamp Included
BL400P8WAEXUPL	BL-400P8-WA22-WH-EX-UPL	400	Quad-Tap	Mogul	Lamp Included
HIGH PRESSURE SODIUM					
BL400S8WHWAUPL	BL-400S8-WH-WA-UPL	400	Quad-Tap	Mogul	Lamp Included

ORDERING INFORMATION

OPTIONS FOR SUPERBAY SERIES

Factory installed — order with fixture by adding suffix.

PLUGS ARE TWIST-LOCK® TYPE AS MANUFACTURED BY HUBBELL WIRING DEVICES.

Suffix	Description
-CFB	Charcoal filter breather
-C4HL	4' Cord, Hook/Loop w/ Quick-On® Hanger - SO cord wired thru hook
-C6HL	6' Cord, Hook/Loop w/ Quick-On® Hanger - SO cord wired thru hook
-C8HL	8' Cord, Hook/Loop w/ Quick-On® Hanger - SO cord wired thru hook
-C10HL	10' Cord, Hook/Loop w/ Quick-On® Hanger - SO cord wired thru hook
-C12HL	12' Cord, Hook/Loop w/ Quick-On® Hanger - SO cord wired thru hook

CORD, HOOK/LOOP & 20A PLUG W/ QUICK-ON® HANGER -
SO CORD W/ PLUG WIRED THRU HOOK

LENGTH	X=	120V	208V	240V	277V	480V	347V
-C4HLP (X)	4'	1	2	3	4	5	C
-C6HLP (X)	6'	1	2	3	4	5	C
-C8HLP (X)	8'	1	2	3	4	5	C
-C10HLP (X)	10'	1	2	3	4	5	C
-C12HLP (X)	12'	1	2	3	4	5	C

CORD, HOOK/LOOP & 15A PLUG W/ QUICK-ON® HANGER -
SO CORD W/ PLUG WIRED THRU HOOK

LENGTH	X=	120V	208V	240V	277V	480V	347V
-C4HLPX-15A	4'	1	2	3	4	5	C
-C6HLPX-15A	6'	1	2	3	4	5	C
-C8HLPX-15A	8'	1	2	3	4	5	C
-C10HLPX-15A	10'	1	2	3	4	5	C
-C12HLPX-15A	12'	1	2	3	4	5	C

-C4HLP1-15A	4' Cord, Hook/Loop & 15A 120V Plug w/ Quick-On® Hanger - SO cord w/ plug wired thru hook
-C6HLP1-15A	6' Cord, Hook/Loop & 15A 120V Plug w/ Quick-On® Hanger - SO cord w/ plug wired thru hook
-C8HLP1-15A	8' Cord, Hook/Loop & 15A 120V Plug w/ Quick-On® Hanger - SO cord w/ plug wired thru hook
-C10HLP1-15A	10' Cord, Hook/Loop & 15A 120V Plug w/ Quick-On® Hanger - SO cord w/ plug wired thru hook
-C12HLP1-15A	12' Cord, Hook/Loop & 15A 120V Plug w/ Quick-On® Hanger - SO cord w/ plug wired thru hook
-C4HLP4-15A	4' Cord, Hook/Loop & 15A 277V Plug w/ Quick-On® Hanger - SO cord w/ plug wired thru hook
-C6HLP4-15A	6' Cord, Hook/Loop & 15A 277V Plug w/ Quick-On® Hanger - SO cord w/ plug wired thru hook
-C8HLP4-15A	8' Cord, Hook/Loop & 15A 277V Plug w/ Quick-On® Hanger - SO cord w/ plug wired thru hook
-C10HLP4-15A	10' Cord, Hook/Loop & 15A 277V Plug w/ Quick-On® Hanger - SO cord w/ plug wired thru hook
-C12HLP4-15A	12' Cord, Hook/Loop & 15A 277V Plug w/ Quick-On® Hanger - SO cord w/ plug wired thru hook

CORD, HOOK/LOOP & 20A PLUG W/ SLICK-ON® HANGER -
SO CORD W/ PLUG WIRED THRU HOOK

LENGTH	X=	120V	208V	240V	277V	480V	347V
-C4HLP50 (X)	4'	1	2	3	4	5	C
-C6HLP50 (X)	6'	1	2	3	4	5	C
-C8HLP50 (X)	8'	1	2	3	4	5	C
-C10HLP50 (X)	10'	1	2	3	4	5	C
-C12HLP50 (X)	12'	1	2	3	4	5	C

Suffix	Description
-C4HLP501-15A	4' Cord, Hook/Loop & 15A 120V Plug w/ Slick-On® Hanger - SO cord w/ plug wired thru hook
-C6HLP501-15A	6' Cord, Hook/Loop & 15A 120V Plug w/ Slick-On® Hanger - SO cord w/ plug wired thru hook
-C8HLP501-15A	8' Cord, Hook/Loop & 15A 120V Plug w/ Slick-On® Hanger - SO cord w/ plug wired thru hook
-C10HLP501-15A	10' Cord, Hook/Loop & 15A 120V Plug w/ Slick-On® Hanger - SO cord w/ plug wired thru hook
-C12HLP501-15A	12' Cord, Hook/Loop & 15A 120V Plug w/ Slick-On® Hanger - SO cord w/ plug wired thru hook
-C4HLP504-15A	4' Cord, Hook/Loop & 15A 277V Plug w/ Slick-On® Hanger - SO cord w/ plug wired thru hook
-C6HLP504-15A	6' Cord, Hook/Loop & 15A 277V Plug w/ Slick-On® Hanger - SO cord w/ plug wired thru hook
-C8HLP504-15A	8' Cord, Hook/Loop & 15A 277V Plug w/ Slick-On® Hanger - SO cord w/ plug wired thru hook
-C10HLP504-15A	10' Cord, Hook/Loop & 15A 277V Plug w/ Slick-On® Hanger - SO cord w/ plug wired thru hook
-C12HLP504-15A	12' Cord, Hook/Loop & 15A 277V Plug w/ Slick-On® Hanger - SO cord w/ plug wired thru hook

CORD, HOOK/LOOP & 20A PLUG W/ SLICK-ON® HANGER -
SINGLE FUSE (incl.) SO CORD W/ PLUG WIRED THRU HOOK

LENGTH	X3=	120V	277V	347V
-C4HLP50F (X3)	4'	1	4	C
-C6HLP50F (X3)	6'	1	4	C
-C8HLP50F (X3)	8'	1	4	C
-C10HLP50F (X3)	10'	1	4	C
-C12HLP50F (X3)	12'	1	4	C

CORD, HOOK/LOOP & 20A PLUG W/ SLICK-ON® HANGER -
DOUBLE FUSE (incl.) SO CORD W/ PLUG WIRED THRU HOOK

LENGTH	X4=	208V	240V	480V
-C4HLP50FF (X4)	4'	2	3	5
-C6HLP50FF (X4)	6'	2	3	5
-C8HLP50FF (X4)	8'	2	3	5
-C10HLP50FF (X4)	10'	2	3	5
-C12HLP50FF (X4)	12'	2	3	5

-C4HLSO	4' Cord & Hook/Loop w/ Slick-On® Hanger - SO cord wired thru hook
-C6HLSO	6' Cord & Hook/Loop w/ Slick-On® Hanger - SO cord wired thru hook
-C8HLSO	8' Cord & Hook/Loop w/ Slick-On® Hanger - SO cord wired thru hook
-C10HLSO	10' Cord & Hook/Loop w/ Slick-On® Hanger - SO cord wired thru hook
-C12HLSO	12' Cord & Hook/Loop w/ Slick-On® Hanger - SO cord wired thru hook

Suffix	Description
	CORD, HOOK/LOOP W/ SLICK-ON® HANGER - SINGLE FUSE (incl.) SO CORD W/ PLUG WIRED THRU HOOK
	LENGTH X2= 120V 277V 347V
-C4HLSOF (X2)	4' 1 4 C
-C6HLSOF (X2)	6' 1 4 C
-C8HLSOF (X2)	8' 1 4 C
-C10HLSOF (X2)	10' 1 4 C
-C12HLSOF (X2)	12' 1 4 C

Suffix	Description
	FLEXIBLE WIRE SYSTEM FIXTURE CORD (CANADA ONLY)
-GR	Gray Lektrocote® Finish on housing; replace -WH in catalog number
-LRI¹	Lower Luminaire Retainer - a snap-in cable on housing secures reflector to ballast housing
-QSS	Quartz Standby System - ON when power is restored, OFF when HID lamp restrikes. Wattage of quartz lamp (not incl.) may not exceed wattage of HID lamp (250W max. recommended). Uses 120V DC bayonet base lamp. Factory wired.
-QST	Quartz Standby with Time Delay - ON when power is restored, OFF when HID lamp restrikes and is warmed up. Wattage not to exceed wattage of HID lamp (250W max. recommended). Uses 120V DC bayonet base lamp. Factory wired.
-SO	Slick-On® Thru Wire Outlet Box for 3/4" pendant or 1/2" or 3/4" side entry conduit
	SLICK-ON® THRU WIRE OUTLET BOX, SINGLE FUSE (incl.) for 3/4" pendant or side entry conduit
	X3= 120V 277V 347V
-SOF (X3)	1 4 F
	SLICK-ON® THRU WIRE OUTLET BOX, DOUBLE FUSE (incl.) for 3/4" pendant or side entry conduit (not for Canada)
	X4= 208V 240V 480V
-SOFF (X4)	2 3 5
-TRI(X)	Top Luminaire Retainer - chain secures ballast housing to structure when additional safety precautions are required. Shipped in housing carton. Specify length (X), recommended maximum slack is 3"

¹ Luminaire retainers/safety cables reduce risk of equipment falling

NOTE: For specific applications, bottom enclosures may be required. For more information, please see specific lamp manufacturers' data and the NEMA white paper "Best Practices for Metal Halide Lighting Systems" posted on the NEMA web site (www.nema.org).

WARNING: Improper selection, installation, operation, servicing, removal, and disposal of lighting products may create serious hazardous including fires, explosions, shock, burns, cuts, impaired vision, falling objects, and environmental contamination. Reduce risks by using the guidance of licensed professionals throughout the product life cycle, and following individual product, component, and accessory safety instructions and labels.

We offer this in the interest of safety for our customers, who may not be aware of the potentially high risk involved in the misuse of these products.

ORDERING INFORMATION

ACCESSORIES

(order separately)

Catalog #	Description
B-LLR¹	Lower Luminaire Retainer - 2' cable secures reflector to ballast housing
B-TLR(6)¹	6' Top Luminaire Retainer - chain secures ballast housing to structure when additional safety precautions are required
B-TLR(10)¹	10' Top Luminaire Retainer - chain secures ballast housing to structure when additional safety precautions are required
B-TLR(12)¹	12' Top Luminaire Retainer - chain secures ballast housing to structure when additional safety precautions are required
B-TLR(16)¹	16' Top Luminaire Retainer - chain secures ballast housing to structure when additional safety precautions are required
WA2-ENC²	22" Acrylic Lens, corrosion-resistant steel lens ring (not dust tight) required for 175, 250, 320 & 350 watt metal halide luminaires; for WA22, WD22 & WW22 reflectors only
BL-QO	Quick-On ³ / ₄ " pendant mount
BL-SO	Slick-On Thru Wire Outlet Box for ³ / ₄ " pendant or ³ / ₄ , ¹ / ₂ side entry conduit
BL-SOF	Slick-On Single Fusing (fuse not incl.) thru wire outlet box for ³ / ₄ " pendant or ³ / ₄ , ¹ / ₂ side entry conduit mount with single fuse holder
BL-SOFF	Slick-On Double Fusing (fuses not incl.) thru wire outlet box for ³ / ₄ " pendant or ³ / ₄ , ¹ / ₂ side entry conduit mount with double fuse holder (not for Canada)
WG-23	23" Wireguard - corrosion resistant, welded steel w/ center lamp access

¹ Luminaire retainers/safety cables reduce risk of equipment falling.

² Bottom enclosures are required unless lamps designated as "suitable for open use" are used.

MOUNTING ACCESSORIES

(order separately)

PLUGS ARE TWIST-LOCK® TYPE AS MANUFACTURED BY HUBBELL WIRING DEVICES.

Catalog #	Description
BLA-C4HLP-1	4' Cord, Hook/Loop and 120V 20A Twist-Lock® Plug
BLA-C4HLP-4	4' Cord, Hook/Loop and 277V 20A Twist-Lock® Plug
BLA-C4HLP1-15A	4' Cord, Hook/Loop and 120V 15A Twist-Lock® Plug
BLA-C4HLP4-15A	4' Cord, Hook/Loop and 277V 15A Twist-Lock® Plug
HOOK/LOOP¹	Hook - cast aluminum ³ / ₄ " NPS male; includes safety screw; converts to Loop with strap included
H3/4AL3/4¹	Swivel Aligner - complete with box for thru wiring; all hubs tapped for ³ / ₄ " conduit - 25° swivel

¹ CSA certified.

² Cord, Hook/Loop and Plug must be added to fixture as option, example: **-C2HLP4**.

³ Cord, Hook/Loop and Dead Front Plug must be added to fixture as option, example: **-DFP4**.

NOTE: Cord used with above accessories is 16/3 SOWA 105°C NEMA configurations.

Due to our continued efforts to improve our products, product specifications are subject to change without notice.



Hubbell Industrial Lighting • 701 Millennium Boulevard • Greenville, SC 29607 • PHONE: 864-678-1000

For more information visit our web site: www.hubbell-itg.com