691186

The precision bored and honed milling head, coupled with the hardened and ground 8" x 36" table ensures retention of tolerances, while locks on all moving surfaces increase user safety. The JET JVM-836 has features you've come to expect that are backed by the industry-leading JET Two Year Warranty

FEATURES

- Precision bored and honed milling head
- · Large diameter quill is chromed
- High precision spindle bearings
- · Over 10" of front to back ram travel
- · Locks on all movable surfaces
- · Hardened and ground precision table
- · Head tilts left or right
- Graduated scale on column
- · Precision ground dovetail ways
- · One shot lubrication system
- · Way covers
- Draw bar
- · Tool box and tools



JET RED ASSURANCE 2-YEAR WARRANTY

JET warrants every product it sells. If one of our tools needs service or repair, one of our Authorized Service Centers located throughout the United States can give you quick service. In most cases, any of these JPW Industries Authorized Service Centers can authorize warranty repair, assist you in obtaining parts, or perform routine maintenance and major repair on your JET tools. For the name of an Authorized Service Center in your area call 1-800-274-6848.

STAND BEHIND YOUR WORK™



691186

SPECIFICATIONS

| Spindle Taper (In. x TPI) | R-8 |
|--|----------------|
| Digital Readout | Newall DP700 |
| Number of Axis | 3 (Quill) |
| Powerfeed | X and Y-Axis |
| Table Size (L x W) (In.) | 7-7/8 x 35-3/4 |
| Quill Diameter (In.) | 3-3/8 |
| Number of Spindle Speeds | 10 |
| Range of Spindle Speeds (RPM) | 120 - 1,550 |
| Spindle Travel (In.) | 5 |
| Head Movement (Deg.) | 90 R & L |
| Max Distance Spindle to Table (In.) | 13-3/4 |
| Distance Spindle to Column (Max.) (In.) | 15-3/4 |
| Distance Spindle to Column (Min.) (In.) | 5-1/4 |
| Collet Capacity | 1/8 - 7/8 |
| Table Longitudinal Travel (In.) | 22-1/4 |
| Table Longitudinal Travel With Powerfeed (In.) | 18 |
| Table Cross Travel (In.) | 9-1/2 |



STAND BEHIND YOUR WORK™



691186

FULL SERIES

| STOCK NO | MODEL NO | SPINDLE TAPER (IN. X TPI) | DIGITAL READOUT | NUMBER OF AXIS | POWERFEED | POWER DRAW BAR |
|----------|-----------|---------------------------|-----------------|----------------|--------------|----------------|
| 690036 | JVM-836-1 | R-8 | | | | |
| 690156 | JVM-836-1 | R-8 | | | X-Axis | |
| 690211 | JVM-836-1 | R-8 | | | X and Y-Axis | |
| 690239 | JVM-836-1 | R-8 | ACU-RITE VUE | 2 | | |
| 690198 | JVM-836-1 | R-8 | ACU-RITE VUE | 2 | X-Axis | |
| 690213 | JVM-836-1 | R-8 | ACU-RITE VUE | 3 (Quill) | X-Axis | |
| 690212 | JVM-836-1 | R-8 | ACU-RITE VUE | 2 | X and Y-Axis | |
| 690177 | JVM-836-1 | R-8 | ACU-RITE 200S | 2 | | |
| 690144 | JVM-836-1 | R-8 | ACU-RITE 200S | 2 | X-Axis | |
| 690162 | JVM-836-1 | R-8 | ACU-RITE 200S | 2 | X and Y-Axis | |
| 691173 | JVM-836-1 | R-8 | Newall DP700 | 2 | | |
| 691174 | JVM-836-1 | R-8 | Newall DP700 | 2 | X-Axis | |
| 691175 | JVM-836-1 | R-8 | Newall DP700 | 2 | X and Y-Axis | |
| 691176 | JVM-836-1 | R-8 | Newall DP700 | 3 (Quill) | | |
| 691177 | JVM-836-1 | R-8 | Newall DP700 | 3 (Quill) | X-Axis | |
| 691178 | JVM-836-1 | R-8 | Newall DP700 | 3 (Quill) | X and Y-Axis | |
| 691228 | JVM-836-1 | R-8 | Newall DP700 | 3 (Knee) | | |
| 690038 | JVM-836-3 | R-8 | | | | |
| 690174 | JVM-836-3 | R-8 | | | X-Axis | |
| 690175 | JVM-836-3 | R-8 | | | X and Y-Axis | |
| 690191 | JVM-836-3 | R-8 | ACU-RITE VUE | 2 | | |
| 690194 | JVM-836-3 | R-8 | ACU-RITE VUE | 2 | X-Axis | |



691186

FULL SERIES

| STOCK NO | MODEL NO | SPINDLE TAPER (IN. X TPI) | DIGITAL READOUT | NUMBER OF AXIS | POWERFEED | POWER DRAW BAR |
|----------|-----------|---------------------------|-----------------|----------------|--------------|----------------|
| 690146 | JVM-836-3 | R-8 | ACU-RITE 200S | 2 | X-Axis | |
| 690047 | JVM-836-3 | R-8 | ACU-RITE 200S | 3 (Knee) | X and Y-Axis | |
| 691179 | JVM-836-3 | R-8 | Newall DP700 | 2 | | |
| 691180 | JVM-836-3 | R-8 | Newall DP700 | 2 | X-Axis | |
| 691183 | JVM-836-3 | R-8 | Newall DP700 | 2 | X and Y-Axis | |
| 691184 | JVM-836-3 | R-8 | Newall DP700 | 3 (Quill) | | |
| 691185 | JVM-836-3 | R-8 | Newall DP700 | 3 (Quill) | X-Axis | |
| 691186 | JVM-836-3 | R-8 | Newall DP700 | 3 (Quill) | X and Y-Axis | |

