SAFETY DATA SHEET

SC0848000

Section 1. Identification

| Product name | : EL™848 Heavy Duty Flash Free® Electrical Solvent Aerosol |
|--|---|
| Product code | : SC0848000 |
| Other means of identification | : Not available. |
| CAS # | : Not applicable. |
| Product type | : Aerosol. |
| Relevant identified uses of t | he substance or mixture and uses advised against |
| Not applicable. | |
| Manufacturer | : Sprayon Products Group 101 W. Prospect Avenue, Cleveland, OHIO 44115 |
| National contact | : Sprayon Products 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada |
| Emergency telephone number of the company | : US / Canada: (216) 566-2917 Mexico: SETIQ 01-800-00-214-00 / D.F. 5559-1588 24 hours / 365 days a year |
| Product Information Telephone Number | : US / Canada: (800) 247-3266 Mexico: Not Available |
| Regulatory Information Telephone Number | : US / Canada: (216) 566-2902 Mexico: Not Available |
| Transportation Emergency Telephone Number | : US / Canada: (800) 424-9300 Mexico: SETIQ 01-800-00-214-00 / D.F. 5559-1588 24 hours / 365 days a year |

Section 2. Hazards identification

| Classification of the substance or mixture | : GASES UNDER PRESSURE - Compressed gas SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A GERM CELL MUTAGENICITY - Category 2 CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract |
|--|--|
| | irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 |
| | Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 2.5% Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 2.5% Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 2.5% |

GHS label elements

Section 2. Hazards identification

| Hazard pictograms | |
|----------------------------------|---|
| Signal word | : Danger |
| Hazard statements | Contains gas under pressure; may explode if heated. Causes serious eye irritation. Causes skin irritation. May cause cancer. Suspected of causing genetic defects. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. |
| Precautionary statements | |
| Prevention | : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Wash hands thoroughly after handling. |
| Response | : Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. |
| Storage | : Store locked up. Protect from sunlight. Store in a well-ventilated place. |
| Disposal | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. |
| | Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

| Substance/mixture | : Mixture |
|-------------------|------------------|
| Other means of | : Not available. |
| identification | |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|-------------------|-------------|------------|
| Trichloroethylene | 97.5 | 79-01-6 |
| Carbon Dioxide | 2.5 | 124-38-9 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

| Date of issue/Date of revision : 8/14/2017 | Date of previous issue | : 4/18/2017 | Version : 3 | 2/13 |
|--|------------------------|-------------|-------------|------|
|--|------------------------|-------------|-------------|------|

Section 4. First aid measures

| Description of necessa | ry first aid measures |
|------------------------|---|
| Eye contact | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Skin contact | : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |

Most important symptoms/effects, acute and delayed

Potential acute health effects

| Eye contact | : Causes serious eye irritation. |
|------------------------------|---|
| Inhalation | Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation. |
| Skin contact | : Causes skin irritation. |
| Ingestion | : Can cause central nervous system (CNS) depression. |
| <u>Over-exposure signs/s</u> | <u>ymptoms</u> |
| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness |
| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : No specific data. |

Indication of immediate medical attention and special treatment needed, if necessary

|--|

Section 4. First aid measures

| Notes to physician | In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
|----------------------------|---|
| Specific treatments | : No specific treatment. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

See toxicological information (Section 11)

| Section 5. Fire-fighting measures | | |
|--|--|--|
| Extinguishing media | | |
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. | |
| Unsuitable extinguishing media | : None known. | |
| Specific hazards arising from the chemical | : In a fire or if heated, a pressure increase will occur and the container may burst. Bursting aerosol containers may be propelled from a fire at high speed. | |
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds carbonyl halides | |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. | |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. | |

Section 6. Accidental release measures

| Personal precautions, protective equipment and emergency procedures | | | |
|---|---|---|--|
| For non-emergency personnel | : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. | |
| For emergency responders | : | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". | |
| Environmental precautions | : | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). | |

Methods and materials for containment and cleaning up

| Date of issue/Date of revision : 8/14/2017 | Date of previous issue | : 4/18/2017 | Version : 3 | 4/13 |
|--|------------------------|-------------|-------------|------|
|--|------------------------|-------------|-------------|------|

Section 6. Accidental release measures

| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
|-------------|---|
| Large spill | : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |

Section 7. Handling and storage

Precautions for safe handling

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Empty containers retain product residue and can be hazardous. |
|--|---|
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| Conditions for safe storage, including any incompatibilities | : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

| Ingredient name | | | Exposure limits |
|---|-------------|---|------------------------------|
| TrichloroethyleneOSHA PEL Z2 (Un TWA: 100 ppm 8 CEIL: 200 ppm AMP: 300 ppm 5 ACGIH TLV (Unite TWA: 10 ppm 8 h STEL: 25 ppm 15Carbon DioxideACGIH TLV (Unite Depletion [Asphy: TWA: 5000 ppm 8 TWA: 9000 mg/m STEL: 30000 ppm STEL: 30000 ppm TWA: 5000 ppm 7 TWA: 5000 ppm 7 | | OSHA PEL Z2 (United States, 2/2013). TWA: 100 ppm 8 hours. CEIL: 200 ppm AMP: 300 ppm 5 minutes. ACGIH TLV (United States, 3/2016). TWA: 10 ppm 8 hours. STEL: 25 ppm 15 minutes. ACGIH TLV (United States, 3/2016). Oxygen | |
| | | Depletion [Asphyxiant]. TWA: 5000 ppm 8 hours. TWA: 9000 mg/m ³ 8 hours. STEL: 30000 ppm 15 minutes. STEL: 54000 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2016). TWA: 5000 ppm 10 hours. TWA: 9000 mg/m ³ 10 hours. STEL: 30000 ppm 15 minutes. | |
| Date of issue/Date of revision | : 8/14/2017 | Date of previous issue | : 4/18/2017 Version : 3 5/13 |

Section 8. Exposure controls/personal protection

| STEL: 54000 mg/m ³ 15 minutes. OSHA PEL (United States, 6/2016). |
|--|
| TWA: 5000 ppm 8 hours. TWA: 9000 mg/m ³ 8 hours. |

Occupational exposure limits (Canada)

| Ingredient name | Exposure limits |
|-------------------|--|
| Trichloroethylene | CA Alberta Provincial (Canada, 4/2009). 15 min OEL: 537 mg/m³ 15 minutes. 15 min OEL: 100 ppm 15 minutes. 8 hrs OEL: 50 ppm 8 hours. 8 hrs OEL: 269 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 7/2016). TWA: 10 ppm 8 hours. STEL: 25 ppm 15 minutes. CA Ontario Provincial (Canada, 7/2015). TWA: 10 ppm 8 hours. STEL: 25 ppm 15 minutes. CA Québec Provincial (Canada, 1/2014). TWAEV: 50 ppm 8 hours. STEV: 200 ppm 15 minutes. STEV: 200 ppm 15 minutes. STEV: 1070 mg/m³ 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 100 ppm 15 minutes. TWA: 50 ppm 8 hours. |

Occupational exposure limits (Mexico)

| Ingredient name | Exposure limits | |
|-------------------|---|--|
| Trichloroethylene | NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 10 ppm 8 hours. STEL: 25 ppm 15 minutes. | |

| Appropriate engineering controls | se only with adequate ventilation. Use process enclosures, local exhaunce ner engineering controls to keep worker exposure to airborne contamir commended or statutory limits. | |
|------------------------------------|---|-----------------------------|
| Environmental exposure controls | nissions from ventilation or work process equipment should be checke ey comply with the requirements of environmental protection legislatior ses, fume scrubbers, filters or engineering modifications to the proces Il be necessary to reduce emissions to acceptable levels. | n. In some |
| Individual protection measured | | |
| Hygiene measures | ash hands, forearms and face thoroughly after handling chemical prod ting, smoking and using the lavatory and at the end of the working per opropriate techniques should be used to remove potentially contaminat ash contaminated clothing before reusing. Ensure that eyewash static owers are close to the workstation location. | iod. ed clothing. |
| Eye/face protection | afety eyewear complying with an approved standard should be used wh sessment indicates this is necessary to avoid exposure to liquid splash uses or dusts. If contact is possible, the following protection should be assessment indicates a higher degree of protection: chemical splash | nes, mists, worn, unless |
| Skin protection | | |
| | | |

Section 8. Exposure controls/personal protection

| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
|------------------------|--|
| Body protection | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. |

Section 9. Physical and chemical properties

| Physical state: Liquid.Color: Not available.Odor: Not available.Odor threshold: Not available.pH: Not available.Melting point: Not available.Boiling point: Not available.Flash point: Not available.Flash point: Closed cup: >93.3°C (>199.9°F)Evaporation rate: 5 (butyl acetate = 1)Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Lower: 12.5% Upper: 90%Vapor pressure: 101.3 kPa (760 mm Hg) [at 20°C]Vapor density: 4.53 [Air = 1] |
|---|
| Odor: Not available.Odor threshold: Not available.pH: Not available.Melting point: Not available.Boiling point: Not available.Flash point: Closed cup: >93.3°C (>199.9°F)Evaporation rate: 5 (butyl acetate = 1)Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Lower: 12.5% Upper: 90%Vapor pressure: 101.3 kPa (760 mm Hg) [at 20°C] |
| Odor threshold: Not available.pH: Not available.Melting point: Not available.Boiling point: Not available.Flash point: Closed cup: >93.3°C (>199.9°F)Evaporation rate: 5 (butyl acetate = 1)Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Lower: 12.5% Upper: 90%Vapor pressure: 101.3 kPa (760 mm Hg) [at 20°C] |
| pH: Not available.Melting point: Not available.Boiling point: Not available.Flash point: Closed cup: >93.3°C (>199.9°F)Evaporation rate: 5 (butyl acetate = 1)Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Lower: 12.5% Upper: 90%Vapor pressure: 101.3 kPa (760 mm Hg) [at 20°C] |
| Melting point: Not available.Boiling point: Not available.Flash point: Closed cup: >93.3°C (>199.9°F)Evaporation rate: 5 (butyl acetate = 1)Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Lower: 12.5% Upper: 90%Vapor pressure: 101.3 kPa (760 mm Hg) [at 20°C] |
| Boiling point: Not available.Flash point: Closed cup: >93.3°C (>199.9°F)Evaporation rate: 5 (butyl acetate = 1)Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Lower: 12.5% Upper: 90%Vapor pressure: 101.3 kPa (760 mm Hg) [at 20°C] |
| Flash point: Closed cup: >93.3°C (>199.9°F)Evaporation rate: 5 (butyl acetate = 1)Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Lower: 12.5% Upper: 90%Vapor pressure: 101.3 kPa (760 mm Hg) [at 20°C] |
| Evaporation rate: 5 (butyl acetate = 1)Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Lower: 12.5% Upper: 90%Vapor pressure: 101.3 kPa (760 mm Hg) [at 20°C] |
| Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Lower: 12.5% Upper: 90%Vapor pressure: 101.3 kPa (760 mm Hg) [at 20°C] |
| Lower and upper explosive (flammable) limits: Lower: 12.5% Upper: 90%Vapor pressure: 101.3 kPa (760 mm Hg) [at 20°C] |
| (flammable) limitsUpper: 90%Vapor pressure: 101.3 kPa (760 mm Hg) [at 20°C] |
| |
| Vapor density $\therefore 4.53$ [Air = 1] |
| |
| Relative density : 1.44 |
| Solubility : Not available. |
| Partition coefficient: n- : Not available. octanol/water |
| Auto-ignition temperature : Not available. |
| Decomposition temperature : Not available. |
| Viscosity : Kinematic (40°C (104°F)): <0.205 cm ² /s (<20.5 cSt) |
| Molecular weight : Not applicable. |
| Aerosol product |
| Type of aerosol : Spray |
| Heat of combustion : 0 kJ/g |

Section 10. Stability and reactivity

| | <i>,</i> |
|------------------------------------|--|
| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : No specific data. |
| Incompatible materials | : No specific data. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |
| | |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|---|---------|--|-------------------|
| | LC50 Inhalation Vapor LD50 Dermal LD50 Oral | Rabbit | 140700 mg/m³ >20 g/kg 4920 mg/kg | 1 hours - - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|---------------------------|-------------|
| Trichloroethylene | Eyes - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| | Skin - Severe irritant | Rabbit | - | 24 hours 2 milligrams | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|---------------------------------|
| Trichloroethylene | - | 1 | Known to be a human carcinogen. |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Section 11. Toxicological information | | | | |
|---------------------------------------|------------|-------------------|---|--|
| Name | Category | Route of exposure | Target organs | |
| Trichloroethylene | Category 3 | Not applicable. | Respiratory tract irritation and Narcotic effects | |

Specific target organ toxicity (repeated exposure)

| Name | | Route of exposure | Target organs |
|-------------------|------------|----------------------|----------------|
| Trichloroethylene | Category 2 | Not determined | Not determined |

Aspiration hazard

Not available.

| | . Net evellette |
|--|---|
| Information on the likely routes of exposure | : Not available. |
| Potential acute health effe | <u>ets</u> |
| Eye contact | : Causes serious eye irritation. |
| Inhalation | : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation. |
| Skin contact | : Causes skin irritation. |
| Ingestion | : Can cause central nervous system (CNS) depression. |
| Symptoms related to the p | hysical, chemical and toxicological characteristics |
| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness |
| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : No specific data. |
| <u>Delayed and immediate eff</u> <u>Short term exposure</u> | ects and also chronic effects from short and long term exposure |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Long term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Potential chronic health ef | fects |
| | |

| Date o | f issue | Date of | revision |
|--------|---------|---------|----------|
|--------|---------|---------|----------|

Date of previous issue : 4/18/2017

Not available.

| General | : May cause damage to organs through prolonged or repeated exposure. |
|-----------------------|---|
| Carcinogenicity | : May cause cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : Suspected of causing genetic defects. |
| Teratogenicity | : No known significant effects or critical hazards. |
| Developmental effects | : No known significant effects or critical hazards. |
| Fertility effects | : No known significant effects or critical hazards. |
| | |

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|-------|--------------|
| Oral | 5046.2 mg/kg |

Section 12. Ecological information

| <u>Toxicity</u> | | | |
|-------------------------|--|--|----------------------------------|
| Product/ingredient name | Result | Species | Exposure |
| Trichloroethylene | Acute EC50 95000 µg/l Marine water Acute EC50 36.5 mg/l Fresh water | Algae - Skeletonema costatum Algae - Chlamydomonas reinhardtii - Exponential growth phase | 96 hours 72 hours |
| | Acute LC50 20 mg/l Marine water Acute LC50 18000 μg/l Fresh water Acute LC50 3100 μg/l Fresh water | Crustaceans - Elminius modestus Daphnia - Daphnia magna Fish - Jordanella floridae - Juvenile (Fledgling, Hatchling, Weanling) | 48 hours 48 hours 96 hours |
| | Chronic EC10 12.3 mg/l Fresh water | Algae - Chlamydomonas reinhardtii - Exponential growth phase | 72 hours |
| | Chronic NOEC 2.3 mg/l Fresh water | Daphnia - Daphnia magna | 21 days |

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| Trichloroethylene | - | 17 | low |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

| UN proper AE shipping name | N1950 EROSOLS | UN1950 AEROSOLS | UN1950 AEROSOLS | UN1950 AEROSOLS, NON- FLAMMABLE, TOXIC, CONTAINING | UN1950 AEROSOLS |
|------------------------------|------------------|---|--------------------|---|--|
| shipping name | EROSOLS | AEROSOLS | AEROSOLS | NON- FLAMMABLE, TOXIC, CONTAINING | AEROSOLS |
| Transact 0.0 | | | | SUBSTANCES IN DIVISION 6.1, PACKING GROUP III | |
| Transport 2.2 | 2 | 2.2 | 2.2 | 2.2 (6.1) | 2.2 |
| hazard class(es) | | | | | |
| Packing group - | | - | - | - | - |
| Environmental No. hazards |). | No. | No. | No. | No. |
| Additional - information | | Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2. 13-2.17 (Class 2). | - | - | <u>Emergency</u> <u>schedules</u> F-D, S U |
| ER | RG No. | ERG No. | ERG No. | | |
| 126 | 6 | 126 | 126 | | |

consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the

| Date of issue/Date of revision : 8/14/201 | 7 Date of previous issue | : 4/18/2017 | Version : 3 | 11/13 |
|---|--------------------------|-------------|-------------|-------|
|---|--------------------------|-------------|-------------|-------|

Section 14. Transport information

substances and on all actions in case of emergency situations.

Transport in bulk according : Not available. to Annex II of MARPOL and the IBC Code

| Ship type | : Not available. |
|----------------------|------------------|
| Pollution category | : Not available. |
| Proper shipping name | : Not available. |

Section 15. Regulatory information

U.S. Federal regulations : TSCA 5(a)2 final significant new use rules: Trichloroethylene

SARA 313


SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

| Classification | Justification |
|---|----------------------|
| GASES UNDER PRESSURE - Compressed gas | Calculation method |
| SKIN CORROSION/IRRITATION - Category 2 | Calculation method |
| SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A | Calculation method |
| GERM CELL MUTAGENICITY - Category 2 | Calculation method |
| CARCINOGENICITY - Category 1A | Calculation method |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract | Calculation method |
| irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) Category 3 | - Calculation method |
| SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 | Calculation method |
| <u>History</u> | |
| Date of printing : 8/14/2017 | |
| Date of issue/Date of : 8/14/2017 revision | |

| 11 | 0/14/2011 |
|----|-----------|
| | |
| : | 4/18/2017 |
| 1 | 3 |
| | : |

| Date of | issue/Date | of revision |
|---------|------------|-------------|
|---------|------------|-------------|

Section 16. Other information

| Key to abbreviations | : ATE = Acute Toxicity Estimate |
|----------------------|--|
| | BCF = Bioconcentration Factor |
| | GHS = Globally Harmonized System of Classification and Labelling of Chemicals |
| | IATA = International Air Transport Association |
| | IBC = Intermediate Bulk Container |
| | IMDG = International Maritime Dangerous Goods |
| | LogPow = logarithm of the octanol/water partition coefficient |
| | MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 |
| | as modified by the Protocol of 1978. ("Marpol" = marine pollution) |
| | UN = United Nations |

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.