Three Stage Light Mast on 14 Foot Single Axle Trailer with wheels - Extends up to 30 Feet Part #: LM-30-3S-TLR



Made in the USA

The Larson Electronics LM-30-3S-TLR trailer mounted fold over 3-stage light mast provides a safe and effective way for operators to quickly deploy lights, security cameras and other equipment to elevations up to thirty feet. This light tower folds over for easy transportation, features a rotating boom that allows for 360° of rotation, and a removable mast head for storing mounted equipment when not in use. The entire assembly is mounted onto a 14' single axle trailer, allowing operators to transport this fold over boom from location.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO LIGHT MASTS OR LIGHT TOWERS

This telescoping three stage steel light mast from Larson Electronics' is designed to allow operators to quickly and safely deploy lighting, cameras, and other electrical equipment in locations where this equipment must be elevated to heights up to 30' for effective coverage. This light boom can be extended to 30' above the trailer floor for maximum area coverage, and collapsed to 13.5' for applications where a footprint smaller is required. The tower is constructed of square steel tubing with a lower section 12' in length and 4" by 4" by 1/8" thick, middle section 9.5' in length and 3" by 3" by 1/8" thick, and an upper section 8.5' in length and 2" by 2" by 1/8" thick. Each section has 1' foot of overlap. The mast is elevated using an included 1,000lb rated hand winch with 3/16" galvanized steel cable and extended to its full height using a second 1,000 lbs winch.



44" Mast Head for mounting lights and equipment

Click Image to Enlarge



Click Image to Enlarge



13" by 15" by 1/4" thick mounting base

Click Image to Enlarge



Click Image to Enlarge

Click Image to Enlarge



Click Image to Enlarge

A 44" wide and 2" by 2" by 1/4" thick mounting plate is attached to the upper section of the mast which provides a strong and stable platform for standard payloads up to 150 lbs. When elevated to its full upright position, the mast can be rotated a full 360°. By loosening the T-Handle, operators can rotate the mast with easy in either direction. The mast can be positioned in one of four different positions, and locked back in place by re-tightening the T-handle. The mast itself spins freely with easy, and can typically be rotated with a single hand.

The LM series of towers are powder coated with glossy blue finish for corrosion resistances and aesthetics. This light mast is mounted to a 14' by 6', single axle trailer via six 1/2" anchor bolts. The two wheel trailer is equipped with 5,4000 lbs axle and leaf springs with 15" trailer tires. The trailer can support and haul an additional 3,500 lbs of equipment. A standard 2" ball coupling, two standard safety chains, and 4-pin flat trailer plug allow for easy hookup and towing.

The LM family of telescoping towers feature a proprietary mast guidance system, which provide increased stability during high winds. Four 1,000 Ibs hand crank leveling jacks are used for leveling. The jacks can be leveled by hand crank or attachment provided for power drills. These outriggers can be extended 2' out from the side of the trailer for added stability. When lowered to 13.5', the mast can withstand winds up to 125 mph. Custom builds can be provided for higher wind speed resistance when fully raised.



Retractable outriggers with 1,000 lb manual crank jacks and tail lights.

Click Image to Enlarge



Manual 1,000 lb hand crank winch for elevating Mast support bracket for securing the mast and folding over the light mast on the LM-30-3S-TLR.

boom in the fold-over position during transportation.

Click Image to Enlarge

Click Image to Enlarge





The LM-30-3S-TLR fitted with four HID-22-SL-REM 1000 Watt Metal Halide Light Fixtures

Ready to Ship

Click Image to Enlarge

Click Image to Enlarge

This light tower assembly weighs approximately 1200 lbs, can easily support and lift 150 lbs fixtures. The entire tower assembly is shipped via common freight carrier or flatbed. Larson Electronics can custom tailor these units to the customer's requirements with longer sections and larger mounting plates. For example, the LM-40-4S is another model that reaches to a length of 40', with base section 11.25' in length, lower section 11.25' in length, an upper section 11.25' in length, and a top section 11.75' in length. Larson Electronics can custom build these towers to meet your overall and collapsed height requirements.

We also offer a choice of either the manual or electric winches, finishing, and equipped light heads. Winch options include 1,000 lbs hand winches (included standard) or optional electric winches for standard light towers, and heavy duty winches and hoists for high payload units. Powder coating color can be customized (the standard mast is gloss blue). Mast location on the trailer bed can be tongue mounted, front of the trailer bed, or center of the trailer bed. These towers can be fitted with Larson Electronics line of high output light heads, or customize the mast head to meet the mounting requirements for your equipment.

The LM-30-3S-TLR fitted with four EPL-HB-150LED-RT 150 Watt Explosion Proof LED Light Fixtures

Click Image to Enlarge





Click Image to Enlarge

Click Image to Enlarge

Click Image to Enlarge

Suggested Applications: Temporary lighting, construction sites, and security camera deployment. We can equip this mast with 1000W HID-22-SL-REM or 1500W HID-22-15M-SL-REM Metal Halide lights or a wide variety of high powered LED lights with comparable power, including the LED10WSA-160, LED10WSA-320, LEDP5W-30, LEDP5W-60, and GAU-HB-160LED.

Specifications / Additional Information	
LM-30-3S-TLR Trailer Mounted 3-Stage Light Tower	Quick Summary
Light Mast Specs	13.5' to 30' Light Mast
Tower Length: 13.5' to 30'	Steel Construction
Mast Head Length: 44"	Power Coated Finish
Capacity: 150 lbs	Removable Mast Head
Materials: Steel	(4) 1,000lb Retractable Outriggers
Finish: Powder Coated - Gloss Blue	125 mph Wind Resistance
Operation: (2) 1,000lbs Hand Winches, Electric Optional	Manual or Optional Electric Operation
Cable: 3/16" Galvanized Aircraft Cable	
Trailer Specs	
Materials: Steel	
Trailer Dimensions: 14-L' x 6'-W trailer bed	
Hitch: 2" Ball Coupler	
Wiring: 4-Pin Flat	
Axle: 5,400lb	
Suspension: 5,400 Lb 4-Leaf Double Eye Springs	
Outriggers: (4) 1,000 Manual Crack Leveling Jacks - Retractable	
Wheels: (2) 15" 5x4.5 Steel Rims	
Tires: ST205/75/D15 H188	

	Special Orders- Requirements
Weight: +-1200 lbs	Contact us for special requirements
Shipping: Common Freight	Phone: 1-214-616-6180
Shipping Dimensions: ~16.5'-L x 4'-W x 5'-H	Toll Free: 1-800-369-6671
Shipping Weight: +-1700 lbs	Fax: 1-903-498-3364
Options: Length- Mounting-Fixtures/ Call Us for Special Requirements	E-mail: sales@larsonelectronics.com

3 year warranty replacement on this light mast. The customer ships the failed light mast to Larson Electronics at their expense. If the failure is a manufacturer defect, we will repair and/or replace the unit.

Scroll Down to Purchase-

Part #: LM-30-3S-TLR (50943)







Links (Click on the below items to view):

- Hi-Res Image 1 Three Stage Light Mast on 14 Foot Single Axle Trailer Extended
- Hi-Res Image 2 Three Stage Light Mast on 14 Foot Single Axle Trailer Collapsed
- Hi-Res Image 3 Three Stage Light Mast on 14 Foot Single Axle Trailer Raised
- Hi-Res Image 4 Three Stage Light Mast on 14 Foot Single Axle Trailer Side
- Hi-Res Image 5 Three Stage Light Mast on 14 Foot Single Axle Trailer Front
- Hi-Res Image 6 Three Stage Light Mast on 14 Foot Single Axle Trailer 3/4 view
- Hi-Res Image 7 Three Stage Light Mast on 14 Foot Single Axle Trailer Back



- Hi-Res Image 8 Three Stage Light Mast on 14 Foot Single Axle Trailer Support Bracket
- Hi-Res Image 9 Three Stage Light Mast on 14 Foot Single Axle Trailer Hand Crank
- Hi-Res Image 10 Three Stage Light Mast on 14 Foot Single Axle Trailer Mast