



RUST BULLET® METAL JACKET™ APPLICATION GUIDELINES

METAL PARTS PROTECTOR

A Removable, Translucent, Rust Inhibitive, Stand-Alone, Protective Coating

Surface Preparation

All surfaces to be treated with Rust Bullet Metal Jacket must be dry and clean, free of any dirt, debris or rust. Do not apply Rust Bullet Metal Jacket over rust or corrosion. Corrosion can and will continue to spread under the coating if not removed.

Mixing and Stirring

Mix or stir to a smooth consistency prior to application. For optimum application results, Rust Bullet Metal Jacket should be at room temperature or warmer during application.

Application Methods

Rust Bullet Metal Jacket may be applied by brush or when appropriate, a dipping process. The recommended 1 - 2 coats will provide complete surface protection. Time between coats of Metal Jacket is approximately 30 minutes. Rust Bullet Metal Jacket never completely dries, remaining oily and greasy to the touch, but will not rub or wipe off. Brush application is no different than with any paint application. Dip by total submersion is also the same process as with any dip application. Product cure time is approximately 4 - 6 hours. Surface protection will last approximately 24 months depending on dry film thickness of application, substrate, exposure, environment, handling, and proper maintenance. Do not apply topcoats of any type over Rust Bullet Metal Jacket.

Removal

Rust Bullet Metal Jacket can be easily removed with Rust Bullet Solvent, mineral spirits or mild alkaline cleaners.

Storage

Store Metal Jacket in a cool, dry, well-ventilated location between 32°F (0°C) and 110°F (43°C) away from heat or open Flame. Do not store at temperatures above 120° F.

Handling & Safety

Use with adequate ventilation, and if necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states. Ensure eyewash/safety shower stations are available near areas where this product is used. Avoid getting product on skin or ingesting product. Wash thoroughly after handling. Keep away from incompatibles such as oxidizing agents and alkalis. IMPORTANT: Protective clothing, gloves, and eye protection are recommended when using Rust Bullet Metal Jacket.

For more complete coverage of safety issues refer to the GHS SDS at www.RustBullet.com

Information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Rust Bullet, LLC (the Company), disclaims any liability incurred in connection with the use of our products and information contained herein. No person is authorized or empowered to make any statement or recommendation not contained herein, any such statement or recommendation so made shall not bind the Company. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use. The information is furnished upon the condition that the recipient shall make their own determination concerning suitability for their particular application.

Rust Bullet LLC ~ 300 Brinkby Avenue, Suite 200 ~ Reno, NV 89509 USA

www.RustBullet.com