Safety Data Sheet



* Trusted Quality Since 1921 * www.rustoleum.com

| 1. Identification | | | |
|----------------------|--|------------------|--|
| Product Name: | SIE S37 5-GL METALMAX SGLOSS ACCENT BASE | Revision Date: | 9/2/2014 |
| Product Identifier: | 208038 | Supercedes Date: | New SDS |
| Product Use/Class: | Tint Base/Sierra S-37 | | |
| Supplier: | Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA | Manufacturer: | Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA |
| Preparer: | Regulatory Department | | |
| Emergency Telephone: | 24 Hour Hotline: 847-367-7700 | | |

2. Hazard Identification

EMERGENCY OVERVIEW: May cause eye, skin, or respiratory tract irritation. KEEP OUT OF REACH OF CHILDREN. Harmful if inhaled. Causes eye irritation. Use ventilation necessary to keep exposures below recommended exposure limits, if any.

Classification

Symbol(s) of Product



Signal Word Warning

GHS HAZARD STATEMENTS

| GIS HAZARD STATEMENTS | | |
|------------------------------------|---------------|--|
| Acute Toxicity, Dermal, category 5 | H313 | May be harmful in contact with skin. |
| Skin Irritation, category 2 | H315 | Causes skin irritation. |
| Aspiration Hazard, category 2 | H305 | May be harmful if swallowed and enters airways. |
| Skin Irritation, category 3 | H316 | Causes mild skin irritation. |
| Eye Irritation, category 2B | H320 | Causes eye irritation. |
| GHS PRECAUTIONARY STATEMENTS | | |
| P102 | Keep out of I | reach of children. |
| P103 | Read label b | before use. |
| P202 | Do not hand | le until all safety precautions have been read and understood. |
| P234 | Keep only in | original container. |
| P260 | Do not breat | he dust/fume/gas/mist/vapours/spray. |
| P261 | Avoid breath | ning dust/fume/gas/mist/vapours/spray. |
| P262 | Do not get in | n eyes, on skin, or on clothing. |
| P264 | Wash thore | oughly after handling. |
| P270 | Do not eat, d | drink or smoke when using this product. |
| P271 | Use only out | doors or in a well-ventilated area. |
| P273 | Avoid releas | e to the environment. |
| | | |

| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
|-----------|--|
| P281 | Use personal protective equipment as required. |
| P285 | In case of inadequate ventilation wear respiratory protection. |
| P312 | Call a POISON CENTER or doctor/physician if you feel unwell. |
| P335 | Brush off loose particles from skin. |
| P351 | Rinse cautiously with water for several minutes. |
| P374 | Fight fire with normal precautions from a reasonable distance. |
| P402 | Store in a dry place. |
| P321 | Specific treatment (see on this label). |
| P352 | Wash with plenty of soap and water. |
| P362 | Take off contaminated clothing and wash before reuse. |
| P332+P313 | If skin irritation occurs: Get medical advice/attention. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P302+P350 | IF ON SKIN: Gently wash with plenty of soap and water. |

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

| <u>Chemical Name</u> | CAS-No. | <u>Wt.%</u> Range | GHS Symbols | GHS Statements |
|----------------------|-----------|----------------------|-------------|----------------|
| Zinc Oxide | 1314-13-2 | 1.0-2.5 | | |
| | 、· · · | | | |

The text for GHS Hazard Statements shown above (if any) is given in the "16. Other Information" section.

4. First-aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, rinse mouth with water. If feeling unwell, get medical attention.

5. Fire-fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted. Keep containers tightly closed.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

7. Handling and Storage

HANDLING: Avoid contact with eyes. Wash hands before eating. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing. **STORAGE:** Keep from freezing. Keep container closed when not in use. Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Page 3/6

8. Exposure Controls/Personal Protection

| Chemical Name | CAS-No. | Weight % Less Than | ACGIH TLV- TWA | ACGIH TLV- STEL | OSHA PEL-TWA | OSHA PEL- CEILING |
|---------------|-----------|-----------------------|------------------------------|-------------------------------|---|----------------------|
| Zinc Oxide | 1314-13-2 | 5.0 | 2 mg/m3 (respirable dust) | 10 mg/m3 (respirable dust) | 5 mg/m3 (respirable dust or fume) | N.E. |

PERSONAL PROTECTION

ENGINEERING CONTROLS: Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Nitrile or Neoprene gloves may afford adequate skin protection. Use gloves to prevent prolonged skin contact.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids. Use ANSI Z87.1 approved safety eyewear.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application. Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

9. Physical and Chemical Properties

| - | - | | |
|-------------------------|-----------------------------|-----------------------------------|-----------------|
| Appearance: | Liquid | Physical State: | Liquid |
| Odor: | Mild | Odor Threshold: | N.E. |
| Relative Density: | 1.098 | pH: | N.D. |
| Freeze Point, °C: | N.D. | Viscosity: | N.D. |
| Solubility in Water: | Miscible | Partition Coefficient, n-octanol/ | No. Information |
| Decompostion Temp., °C: | No Information | water: | No Information |
| Boiling Range, °C: | 115 - 770 | Explosive Limits, vol%: | 16.0 - 25.0 |
| Flammability: | Does not Support Combustion | Flash Point, °C: | >93 |
| Evaporation Rate: | Slower than Ether | Auto-ignition Temp., °C: | No Information |
| Vapor Density: | Heavier than Air | Vapor Pressure: | N.D. |
| | | | |

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid contact with strong acid and strong bases.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: When heated to decomposition, it emits acrid smoke and irritating fumes. By open flame, carbon monoxide and carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye irritation. Irritating, and may injure eye tissue if not removed promptly.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance may cause slight skin irritation. Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INHALATION: Low hazard for usual industrial handling or commercial handling by trained personnel. Routine handling and application does not require use of respiratory protection; however, if air monitoring demonstrates vapor, mist, or dust levels above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during handling and application. Follow respirator manufacturer's directions for respirator use. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed. EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No Information PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

| The acute effects of this product have not been tested. Data on individual components are tabulated below: | | | | |
|--|---------------|-----------------|-------------|------------|
| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 |
| 1314-13-2 | Zinc Oxide | >5000 mg/kg Rat | N.I. | N.I. |

N.I. - No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

14. Transport Information

| | Domestic (USDOT) | International (IMDG) | <u>Air (IATA)</u> | <u>TDG (Canada)</u> |
|-----------------------|------------------|----------------------|-------------------|---------------------|
| UN Number: | N.A. | N.A. | N.A. | N.A. |
| Proper Shipping Name: | Not Regulated | Not Regulated | Not Regulated | Not Regulated |
| Hazard Class: | N.A. | N.A. | N.A. | N.A. |
| Packing Group: | N.A. | N.A. | N.A. | N.A. |
| Limited Quantity: | No | No | No | No |

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| Chemical Name |
|---------------|
|---------------|

Zinc Oxide

CAS-No. 1314-13-2

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

| Chemical Name | CAS-No. |
|--|------------|
| Sodium Nitrite | 7632-00-0 |
| 5-Chloro-2-Methyl-4-Isothiazolin-3-one | 26172-55-4 |
| Methyl-4-Isothiazolin-3-one | 2682-20-4 |
| Acetaldehyde | 75-07-0 |

Inventory Information

Country USA (TSCA) Canada (DSL) Mexico(INSQ) Europe (EINECS) Japan (ENCS) Philippines (PICCS) China (IECSC) Australia (AICS) Korea (KECI) New Zealand (NZIOC)

No Information No Information

Value

No Information

CALIFORNIA PROPOSITION 65:

Warning: This products contains a substance known to the State of California to cause cancer.

No Proposition 65 Carcinogens exist in this product.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: This product contains a substance known to the State of California to cause birth defects or other reproductive harm.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations:

CANADIAN WHMIS:

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

| 16. Other Information | | | | | | | |
|------------------------------------|-------|-----------------|-----------------|---------------------|----|----------------------|---|
| HMIS RAT | | | 0 | Dhusiaal Llamandu | 0 | Descend Drote stien: | × |
| Health: | 1* | Flammability: | 0 | Physical Hazard: | 0 | Personal Protection: | Х |
| CANADIA | | IS CLASS: | D2A | | | | |
| NFPA RAT | rings | | | | | | |
| Health: | 2 | Flammability: | 1 | Instability | 0 | | |
| VOLATILE ORGANIC COMPOUNDS, g/L: 0 | | | | | | | |
| MSDS REVISION DATE: 9/2/2014 | | | | | | | |
| REASON F | OR RE | VISION: | No Information | | | | |
| Legend: N./ | A Not | Applicable, N.E | Not Established | d, N.D Not Determin | ed | | |

Icons for GHS Pictograms shown in Section 3 describing each ingredient: No GHS Pictograms exist for Section 3 Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.