

Safety Data Sheet



* Trusted Quality Since 1921 *
www.rustoleum.com

1. Identification

Product Name:	ROHPER 5-GL V7400 NAVY GRAY	Revision Date:	8/14/2014
Product Identifier:	245444	Supersedes Date:	New SDS
Product Use/Class:	Topcoat/ Alkyd		
Supplier:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA	Manufacturer:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA
Preparer:	Regulatory Department		
Emergency Telephone:	24 Hour Hotline: 847-367-7700		

2. Hazard Identification

EMERGENCY OVERVIEW: Harmful if inhaled. Harmful if swallowed. Causes eye irritation. Flammable liquid and vapor. Causes nose and throat irritation. Use ventilation necessary to keep exposures below recommended exposure limits, if any. Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea. Vapor Harmful. Causes Eye, Skin, Nose, and Throat Irritation. May cause eye, skin, or respiratory tract irritation. KEEP OUT OF REACH OF CHILDREN.

Classification

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

38% of the mixture consists of ingredient(s) of unknown acute toxicity

GHS HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Organic Peroxide, categories C, D	H242	Heating may cause a fire.
Acute Toxicity, Oral, category 2	H300	Fatal if swallowed.
Acute Toxicity, Oral, category 5	H303	May be harmful if swallowed.
Aspiration Hazard, category 2	H305	May be harmful if swallowed and enters airways.
Acute Toxicity, Dermal, category 1	H310	Fatal in contact with skin.
Acute Toxicity, Dermal, category 5	H313	May be harmful in contact with skin.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Eye Irritation, category 2B	H320	Causes eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.

GHS PRECAUTIONARY STATEMENTS

P102	Keep out of reach of children.
P103	Read label before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P220	Keep/Store away from clothing/.../combustible materials.
P234	Keep only in original container.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P262	Do not get in eyes, on skin, or on clothing.
P264	Wash ... thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P285	In case of inadequate ventilation wear respiratory protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+P350	IF ON SKIN: Gently wash with plenty of soap and water.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P321	Specific treatment (see ... on this label).
P322	Specific measures (see ... on this label).
P330	Rinse mouth.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P351	Rinse cautiously with water for several minutes.
P352	Wash with plenty of soap and water.
P361	Remove/Take off immediately all contaminated clothing.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use ... for extinction.
P374	Fight fire with normal precautions from a reasonable distance.
P402	Store in a dry place.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P410	Protect from sunlight.
P411+P235	Store at temperatures not exceeding ...°C/...°F. Keep cool.
P420	Store away from other materials.
P501	Dispose of contents/container to ...

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt.% Range</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Polymers/Binder/Resin	Proprietary	10-25		
1-Chloro-4(Trifluoromethyl)Benzene	98-56-6	10-25	GHS02-GHS06	H226-300-310
Stoddard Solvents	8052-41-3	10-25	GHS02	H224

Mineral Spirits	64742-88-7	2.5-10	GHS06	H331
Octamethylcyclotetrasiloxane	556-67-2	2.5-10	GHS02-GHS06	H226-311
Titanium Dioxide	1317-80-2	1.0-2.5		
Titanium Dioxide	13463-67-7	1.0-2.5		
Ethylbenzene	100-41-4	0.1-1.0	GHS02-GHS07	H225-332
Carbon Black	1333-86-4	0.1-1.0	GHS02	H251

The text for GHS Hazard Statements shown above (if any) is given in the "16. Other Information" section.

4. First-aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention. If swallowed, get medical attention.

5. Fire-fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may explode when exposed to extreme heat due to buildup of steam. Vapors may form explosive mixtures with air. Vapors can travel to a source of ignition and flash back. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. No unusual fire or explosion hazards noted.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Eliminate all ignition sources; use explosion-proof equipment. Place material in a container and dispose of according to local, provincial, state and federal regulations. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of NFPA Class II combustible liquids. Keep away from heat, sparks, flame and sources of ignition. Keep container closed when not in use. Avoid excess heat. Product should be stored in tightly sealed containers and protected from heat, moisture, and foreign materials.

8. Exposure Controls/Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Polymers/Binder/Resin	Proprietary	20.0	N.E.	N.E.	N.E.	N.E.
1-Chloro-4-(Trifluoromethyl) Benzene	98-56-6	20.0	N.E.	N.E.	N.E.	N.E.
Stoddard Solvents	8052-41-3	20.0	100 ppm	N.E.	500 ppm	N.E.
Mineral Spirits	64742-88-7	10.0	100 ppm	N.E.	100 ppm	N.E.
Octamethylcyclotetrasiloxane	556-67-2	5.0	N.E.	N.E.	N.E.	N.E.

Titanium Dioxide	1317-80-2	5.0	10 mg/m ³	N.E.	15 mg/m ³ (Total Dust)	N.E.
Titanium Dioxide	13463-67-7	5.0	10 mg/m ³	N.E.	15 mg/m ³ [Total Dust]	N.E.
Ethylbenzene	100-41-4	1.0	20 ppm	125 ppm	100 ppm	N.E.
Carbon Black	1333-86-4	1.0	3 mg/m ³ (Inhalable Dust)	N.E.	3.5 mg/m ³	N.E.

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications. Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

9. Physical and Chemical Properties

Appearance:	Liquid	Physical State:	Liquid
Odor:	Solvent Like	Odor Threshold:	N.E.
Relative Density:	1.036	pH:	N.A.
Freeze Point, °C:	N.D.	Viscosity:	N.D.
Solubility in Water:	Negligible	Partition Coefficient, n-octanol/ water:	No Information
Decomposition Temp., °C:	No Information	Explosive Limits, vol%:	0.7 - 8.9
Boiling Range, °C:	277 - 500	Flash Point, °C:	37
Flammability:	Supports Combustion	Auto-ignition Temp., °C:	No Information
Evaporation Rate:	Slower than Ether	Vapor Pressure:	N.D.
Vapor Density:	Heavier than Air		

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid temperatures above 120 ° F. Avoid contact with strong acid and strong bases. Avoid all possible sources of ignition.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalis.

HAZARDOUS DECOMPOSITION: By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes Serious Eye Irritation

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated skin contact may cause irritation. Causes skin irritation. Allergic reactions are possible.

EFFECTS OF OVEREXPOSURE - INHALATION: Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if

inhaled. Avoid breathing fumes, spray, vapors, or mist. May cause headaches and dizziness. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Harmful if swallowed. Aspiration hazard if swallowed; can enter lungs and cause damage.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Contains carbon black. Chronic inflammation, lung fibrosis, and lung tumors have been observed in some rats experimentally exposed for long periods of time to excessive concentrations of carbon black and several insoluble fine dust particles. Tumors have not been observed in other animal species (i.e., mouse and hamster) under similar circumstances and study conditions. Epidemiological studies of North American workers show no evidence of clinically significant adverse health effects due to occupational exposure to carbon black.

Carbon black is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC and is proposed to be listed as A4- "not classified as a human carcinogen" by the American Conference of Governmental Industrial Hygienists. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of carbon black in the formula. IARC lists Ethylbenzene as a possible human carcinogen (group 2B). Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
98-56-6	1-Chloro-4-(Trifluoromethyl)Benzene	13 g/kg Rat	>2 mL/kg Rabbit	33 mg/L Rat
64742-88-7	Mineral Spirits	>5000 mg/kg Rat	3000 mg/kg Rabbit	>5.28 mg/L Rat
556-67-2	Octamethylcyclotetrasiloxane	N.I.	794 µL/kg Rabbit	N.I.
13463-67-7	Titanium Dioxide	>10000 mg/kg Rat	N.I.	N.I.
100-41-4	Ethylbenzene	3500 mg/kg Rat	15354 mg/kg Rabbit	17.2 mg/L Rat

N.I. - No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components. Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

14. Transport Information

	<u>Domestic (USDOT)</u>	<u>International (IMDG)</u>	<u>Air (IATA)</u>	<u>TDG (Canada)</u>
UN Number:	1263	1263	1263	1263
Proper Shipping Name:	Paint	Paint	Paint	Paint
Hazard Class:	3	3	3	3
Packing Group:	III	III	III	III
Limited Quantity:	No	No	No	No

15. Regulatory Information

U.S. Federal Regulations:**CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
1-Chloro-4-(Trifluoromethyl)Benzene	98-56-6
Ethylbenzene	100-41-4

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

Inventory Information

<u>Country</u>	<u>Value</u>
USA (TSCA)	No Information
Canada (DSL)	No Information
Mexico(INSQ)	No Information
Europe (EINECS)	No Information
Japan (ENCS)	No Information
Philippines (PICCS)	No Information
China (IECSC)	No Information
Australia (AICS)	No Information
Korea (KECI)	No Information
New Zealand (NZIOC)	No Information

No Information

CALIFORNIA PROPOSITION 65:

Warning: This products contains a substance known to the State of California to cause cancer.

<u>Chemical Name</u>	<u>CAS-No.</u>
Titanium Dioxide	1317-80-2
Titanium Dioxide	13463-67-7
Ethylbenzene	100-41-4
Carbon Black	1333-86-4

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: This product contains a substance known to the State of California to cause birth defects or other reproductive harm.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations:**CANADIAN WHMIS:**

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

16. Other Information

HMIS RATINGS

Health: 2* Flammability: 3 Physical Hazard: 0 Personal Protection: X

CANADIAN WHMIS CLASS: B2 D2A

NFPA RATINGS

Health: 2 Flammability: 3 Instability: 0

VOLATILE ORGANIC COMPOUNDS, g/L: 338

MSDS REVISION DATE: 8/14/2014

REASON FOR REVISION: No Information

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H251	Self-heating; may catch fire.
H300	Fatal if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H332	Harmful if inhaled.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02



GHS06



GHS07



Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.