



**SPILLTECH**

## **MATERIAL SAFETY DATA SHEET**

### **SECTION I: IDENTIFICATION OF PRODUCT**

PRODUCT NAME: PomPom Filament Absorbents  
CHEMICAL FAMILY: Polypropylene

#### **Company Profile:**

SpillTech  
Brookley Industrial Complex  
1627 O'Donoghue Street  
Mobile, AL 36615

**Customer Service Telephone Number:** 1-800-228-3877

**Technical Information Telephone Number:** 1-251-694-0102 ext.121

### **SECTION II: HAZARDOUS INGREDIENTS**

<b><u>INGREDIENTS</u></b>	<b><u>PERCENT</u></b>	<b><u>CAS NUMBER</u></b>	<b><u>OSHA PEL</u></b>	<b><u>ACGIH TLV</u></b>
Polypropylene	100%	9003-07-0	N/A	N/A

### **SECTION III: HAZARDS IDENTIFICATION**

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATING:

HEALTH: 0  
FLAMMABILITY: 1  
REACTIVITY: 0

\*Not considered a hazardous material at temperatures below melting point. Not considered a controlled substance or a carcinogen.

**SECTION IV: FIRST AID MEASURES**

EYE CONTACT: None expected other than possible mechanical irritation.  
SKIN CONTACT: N/A  
INHALATION: N/A  
INGESTION: N/A

**SECTION V: FIRE FIGHTING MEASURES**

FLASH POINT: N/A  
AUTO IGNITION: 390° C (730° F)  
FLAMMABLE LIMITS: N/A  
FIRE EXTINGUISHING MEDIA: Water, Foam, CO2, Dry Chemical  
SPECIAL FIRE FIGHTING PROCEDURES: Standard procedures for Class A fires  
UNUSUAL FIRE AND EXPLOSION HAZARDS: None. Polymerization will not occur; incomplete burning can produce carbon monoxide, carbon dioxide and other harmful products. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

**SECTION VI: ACCIDENTAL RELEASE MEASURES**

No special steps to be taken if material is spilled or released.

**SECTION VII: HANDLING AND STORAGE**

Store in dry area. Do not store near open flame, high heat, strong oxidants, or halogenated hydrocarbons. Polypropylene, when heated, becomes very sticky and will burn. Use self-contained air masks to enter smoky area in the event of fire. Adequate ventilation is required to remove decomposition products when temperature exceeds melting point. Avoid contact with melted product. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

**SECTION VIII: EXPOSURE CONTROLS/ PERSONAL PROTECTION EQUIPMENT**

RESPIRATORY PROTECTION: None Required  
VENTILATION: None Required  
PROTECTIVE GLOVES: None Required  
EYE PROTECTION: Safety glasses with side shields are recommended as a good practice for industrial safety.  
OTHER PROTECTIVE EQUIPMENT (SPECIFY): None Required

**SECTION IX: PHYSICAL DATA**

APPEARANCE AND ODOR:	Green or brown in color & virtually odor free
SPECIFIC GRAVITY:	0.9
BOILING POINT (C):	Not Applicable
MELTING POINT (C):	>160° C (320° F)
SOLUBILITY IN WATER:	Insoluble
PERCENT VOLATILE BY VOLUME:	N/A
EVAPORATION RATE:	N/A
VAPOR PRESSURE (mm Hg):	N/A
VAPOR DENSITY (Air = 1):	N/A

**SECTION X: TRANSPORT INFORMATION**

DOT CLASSIFICATION: Non Hazardous

**SECTION XI: WASTE XI DISPOSAL METHOD**

Disposal must be done in accordance with local, state and federal regulations based on chemicals adsorbed by products.

Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous.

Always refer to the MSDS for the chemical absorbed before proceeding

**SECTION XII: PREPARATION**

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.