




Holo-Krome®
The Difference is Easy To See

800-688-8949 • www.Holo-Krome.com • Sparks, MD

PRODUCT DATA SHEET



Flat Head Socket Cap Screw



Applications:

- Flush mounted applications where one part slides over another
- Flat heads are limited by configuration in their tensile strength capability

Benefits:

- Unified standard threads are Class 3A UNRC and UNRF with Holo-Krome controlled radius roots and radius run-out
- Closely controlled fillet between head and body provides maximum fatigue strength
- Inch Series: ASME/ANSI B18.3 and ASTM F 835
- Metric Series: Reference ISO 10642

Standard Flat Head Socket Cap Screw

Metric Flat Head Socket Cap Screw

DIAMETER	LENGTH UNDER HEAD	PRODUCT CODE NUMBER		DIAMETER	LENGTH UNDER HEAD	PRODUCT CODE NUMBER		DIAMETER	LENGTH UNDER HEAD	PRODUCT CODE NUMBER	DIAMETER	LENGTH UNDER HEAD	PRODUCT CODE NUMBER	
		UNRC	UNRF			UNRC	UNRF							DIAMETER
#4 (.112") 40 UNRC 1/16" Key	1/4"	60002	-	3/8" 16 UNRC 24 UNRF 7/32" Key	1"	60100	61044	M3 Pitch 0.50 2mm Key	6	87003	M10 Pitch 1.50 6mm Key	30	87160	
	3/8"	60004	-		1-1/4"	60102	61046		8	87004		35	87164	
	1/2"	60006	-		1-1/2"	60104	61048		10	87008		40	87168	
	5/8"	60008	-		1-3/4"	60106	-		12	87012		45	87172	
	3/4"	60010	-		2"	60108	-		16	87016		50	87176	
#5 (.125") 40 UNRC 5/64" Key	1/4"	60012	-	7/16" (.437") 14 UNRC 1/4" Key	2-1/4"	60110	-	M4 Pitch 0.70 2.55mm Key	20	87020	M12 Pitch 1.75 8mm Key	60	87177	
	3/8"	60014	-		2-1/2"	60112	-		25	87021		70	87178	
	1/2"	60016	-		3"	60114	-		8	87024		20	87180	
	5/8"	60018	-		3/4"	60116	-		10	87028		25	87184	
	3/4"	60020	-		1"	60118	-		12	87032		30	87188	
#6 (.138") 32 UNRC 5/64" Key	1/4"	60022	-	1/2" (.500") 13 UNRC 20 UNRF 5/16" Key	1-1/4"	60120	-	M5 Pitch 0.80 3mm Key	16	87036	M16 Pitch 2.00 10mm Key	35	87192	
	3/8"	60024	-		1-1/2"	60122	-		20	87040		40	87196	
	1/2"	60026	-		3/4"	60124	61050		25	87044		45	87200	
	5/8"	60028	-		1"	60126	61052		30	87048		50	87204	
	3/4"	60030	-		1-1/4"	60128	61054		35	87049		55	87205	
#8 (.164") 32 UNRC 3/32" Key	3/8"	60032	-	5/8" (.625") 11 UNRC 3/8" Key	1-1/2"	60130	61056	M6 Pitch 1.00 4mm Key	40	87050	M11 Pitch 1.50 6mm Key	60	87206	
	1/2"	60034	-		1-1/2"	60132	61058		8	87052		70	87189	
	5/8"	60036	-		1-3/4"	60134	61060		10	87056		90	87202	
	3/4"	60038	-		2"	60136	-		12	87060		30	87207	
	1"	60040	-		2-1/4"	60138	-		16	87064		35	87208	
#10 (.190") 24 UNRC 32 UNRF 1/8" Key	3/8"	60042	61002	3/4" (.750") 10 UNRC 1/2" Key	2-1/2"	60138	-	M8 Pitch 1.25 5mm Key	20	87068	M13 Pitch 2.00 10mm Key	40	87212	
	1/2"	60044	61004		3"	60140	-		25	87072		45	87213	
	5/8"	60046	61006		1-1/4"	60142	-		30	87076		50	87216	
	3/4"	60048	61008		1-1/2"	60144	-		35	87077		60	87220	
	1"	60050	61010		1-3/4"	60146	-		40	87078		70	87221	
	1-1/4"	60052	61012		2"	60148	-		50	87079				
	1-1/2"	60054	61014		2-1/4"	60150	-		10	87084				
1/4" (.250") 20 UNRC 28 UNRF 5/32" Key	3/8"	60056	61016	5/16" (.312") 18 UNRC 24 UNRF 3/16" Key	2-1/2"	60152	-	M10 Pitch 1.50 6mm Key	12	87088	M14 Pitch 2.00 10mm Key			
	1/2"	60058	61018		3"	60154	-		16	87092				
	5/8"	60060	61020		1-1/2"	60158	-		20	87096				
	3/4"	60062	61022		1-3/4"	60160	-		25	87100				
	1"	60064	61024		2"	60162	-		30	87104				
	1-1/4"	60066	61026		2-1/2"	60166	-		35	87108				
	1-1/2"	60068	61028		3"	60168	-		40	87112				
5/16" (.312") 18 UNRC 24 UNRF 3/16" Key	1-3/4"	60070	-	3/8" 16 UNRC 24 UNRF 7/32" Key				45	87113					
	2"	60072	-					50	87114					
	1/2"	60074	61030					60	87115					
	5/8"	60076	61032					15	87122					
	3/4"	60078	61034					16	87124					
	1"	60080	61036					20	87128					
	1-1/4"	60082	61038					25	87132					
3/8" 16 UNRC 24 UNRF 7/32" Key	1-1/2"	60084	-				30	87136						
	1-3/4"	60086	-				35	87140						
	2"	60088	-				40	87144						
	2-1/4"	60090	-				45	87143						
	2-1/2"	60092	-				50	87145						
							60	87146						
							70	87147						
						15	87151							
						16	87149							
						20	87152							
						25	87156							