

# **N99 PROTECTION**

NIOSH certified to have a filter efficiency of 99% or greater against particulate aerosols free of oil. Suitable for most welding fumes.

# ADJUSTABLE COMFORT

Adjustable cloth straps on 2315N99 allow for a more comfortable fit with a simple tug on the straps. Molded nose bridge with soft foam nose seal fits easily and comfortably without a metal noseband. Exhale valve reduces breathing resistance and hot air buildup. Keeps workers cooler longer.

# LAST LONGER, USE FEWER

The Dura-Mesh® shell protects the filter media so it stays cleaner looking longer. Plus, it resists collapsing, even in heat and humidity so the respirator holds its shape longer. The result is fewer respirators used and lower costs. Meets heat and flame resistance in accordance with ANSI/ISEA 110-2003 Section 7.11.1.

#### **APPLICATIONS**

Welding, soldering, brazing, torch cutting, metal pouring, and dusty environments, i.e., polishing, buffing, lime, poultry and textiles. No oils present.

# **FEATURES**

- 100% PVC-Free
- Can be used against most welding fumes free of oil.
- Adjustable cloth straps assure a snug, comfortable fit.
- Exhale valve lets workers breathe easy and stay cool.
- Exclusive Dura-Mesh® shell resists collapsing in heat and humidity.
- Softspun® lining for increased comfort and durability.
- Fits easily under welding hoods.
- Soft foam nose seal for a comfortable fit.
- Meets heat and flame resistance in accordance with ANSI/ISEA 110-2003 Section 7.11.1.























#### **USE AGAINST:**

1. Particulate aerosols free of oil.

#### **DO NOT USE AGAINST:**

- 1. Concentrations of contaminants which are unknown, or are immediately dangerous to life or health.
- 2. Concentrations of particulates which exceed the maximum use concentration or 10 times the OSHA Permissible Exposure Limit, whichever is lower.
- 3. Gases, vapors, asbestos, paint spray, sandblasting or particulate materials which generate harmful vapors.
- 4. Oil-based mists.

#### **RESTRICTIONS**

- 1. This respirator does not supply oxygen and must not be used in atmospheres containing less than 19.5% oxygen.
- 2. Do not remain in contaminated area if any physical distress occurs, for example breathing difficulty, dizziness or nausea.
- 3. Leave contaminated area and replace respirator if it is damaged, distorted, a proper fit can not be obtained or breathing becomes difficult.
- 4. Prior to each use, carefully inspect the entire respirator, including filter media and strap attachment area for tears and damage. Staple or strap attachment perforations do not effect NIOSH approval.
- 5. Do not alter, modify, or abuse this respirator.
- 6. Store unused respirators in bag in a clean, dry, non-contaminated area.
- 7. Dispose of respirator according to your employer's policy and local regulations.
- 8. Dispose no later than thirty days after first use.
- 9. Use respirator before the "use by" expiration date printed on bag.
- 10. If used for welding, wear appropriate eye and face protection.

#### **TECHNICAL SERVICE HELP LINE**

For technical assistance, call Moldex Tyechnical Service Department at 310/837-6500 ext. 512/550 or 800/421-0668 ext. 512/550.

# **MOLDEX-METRIC, INC.**

10111 W. Jefferson Blvd. Culver City, CA 90232 TEL: 800/421-0668 or 310/837-6500 FAX 310/837-9563 www.moldex.com e-mail: sales@moldex.com

#### **CANADIAN CUSTOMER SERVICE**

TEL: 310-837-6500, Ext. 517 FAX: 310-837-9563

Moldex, Ideas that wear well, Softspun and Dura-Mesh are registered trademarks of Moldex-Metric, Inc. The mesh design is a trademark of Moldex-Metric, Inc. U.S. Patents #D285,374 and #4,850,347 Made in the U.S.A. 9700-711 REV F 10/08



# Moldex-Metric, Inc. CULVER CITY, CALIFORNIA, U.S.A. 800/421-0668



THIS RESPIRATOR IS APPROVED ONLY IN THE FOLLOWING CONFIGURATIONS				
TC-	PROTECTION1	RESPIRATOR		CAUTIONS AND LIMITATIONS <sup>2</sup>
		2310	2315	
84A-1459	N99	Х	х	ABCJMNOP

N99-Particulate Filter (99% filter efficiency level) effective against particulate aerosols free of oil; time use restrictions may apply

- 2. Cautions and Limitations

  A Not for use in atmospheres containing less than 19.5 percent oxygen.

  B Not for use in atmospheres immediately dangerous to life or health.

  C- Do not exceed maximum use concentrations established by regulatory standards.

  J- Fallure to properly use and maintain list product could result in injury or death.

  M. Allapproved respirators shall be selected, fifted, used, and maintained in accordance

  N. Hever substitute, modity, add, or miliparts, Use only exert pelacement parts in the co

  D- Relet to User's Instructions, and/or maintenance manuals for information on use and n

  P. MIOSH does not evaluate registrators a surgical masks.

#### **PACKAGING**

10 Respirators per Bag 6 Bags per Case

# LIMITED WARRANTY IMPORTANT **NOTICE TO PURCHASER**

This limited warranty is made in lieu of the warranties of merchantability, fitness for particular purposes and all other warranties, express or implied. There are no other warranties which extend beyond the description on the face hereof. The physical standards and specifications of Moldex will be met by products sold. Exclusive Remedies: damages for the breach of this limited warranty are limited to the replacement of such quantity of Moldex products proved to be defectively manufactured. Except as provided above, Moldex shall not be liable or responsible for any loss, damages, or liability, direct, indirect, incidental, special or consequential, arising out of a sale, use or misuse, or the inability to use products by the user.

# **WARNING TO USER**

- 1. Follow all instructions and warnings on the use of this respirator and wear during all times of exposure. Failure to do so will reduce respirator effectiveness, wearer protection, and may result in sickness or death.
- ${\bf 2.}\;$  Before use, the user must first be trained by the employer in proper respirator use, in accordance with applicable safety and health standards, for the contaminant and exposure level in the assigned work area.
- The particulates and other contaminants which can be dangerous to your health include those which you cannot see, taste, or smell.
- $\textbf{4.} \ \ \textbf{This product has not been sold with warnings or use instructions for personnel}$ involved in health care or related situations, where there may be the possibility of contact with disease or biological hazards. If you are considering such uses, first call the Moldex Technical Service Dept., 310/837-6500 ext. 512/550 or 800/421-0668 ext. 512/550

## **DISTRIBUTED BY:**





















