



SAFETY DATA SHEET

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: Sakrete Trowelable Crack Filler

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Use: Various.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Sakrete of North Carolina
8201 Arrowridge Blvd.
Charlotte, NC
28273

Telephone Number: 866-725-7383

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number: CHEMTREC 800-424-9300
INTERNATIONAL + 01-703-527-3887

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL

Hazard class

Acute toxicity 4 (Oral)
Skin sensitization 1
Carcinogenicity 1A
Specific target organ toxicity - Repeated exposure 1

2.2 LABEL ELEMENTS

Hazard Pictogram:



Signal Word: Danger

Hazard Statement: Harmful if swallowed. May cause an allergic skin reaction. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Prevention: Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray.



SAFETY DATA SHEET

Response: If swallowed: Immediately call a poison center/doctor. Rinse mouth. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 ADDITIONAL INFORMATION

Hazards not otherwise specified: Not applicable.

11.0 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Ingredient	CAS No	Wt. %
Silica, crystalline, quartz	14808-60-7	15 - 40
Asphalt	8052-42-4	15 - 40
Kaolin	1332-58-7	3 - 7
Mica	12001-26-2	1 - 5
Bentonite	1302-78-9	1 - 5
Aluminatesilicate	1327-36-2	1 - 5
Titanium dioxide	13463-67-7	0.1 - 1
Acetaldehyde	75-07-0	< 0.1
Ethyl acrylate	140-88-5	< 0.1

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Section 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURE

Eye: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

Skin: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.



SAFETY DATA SHEET

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

- Eye:** May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Skin:** May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause skin sensitization.
- Inhalation:** May cause respiratory tract irritation.
- Ingestion:** Harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

- Note to Physicians:** Symptoms may not appear immediately.
- Specific Treatments:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

- Suitable Extinguishing Media:** Treat for surrounding material.
- Unsuitable Extinguishing Media:** Not available.

5.2 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

- Products of Combustion:** May include, and are not limited to: oxides of carbon.

5.3 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

- Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

- Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

- Methods for Containment:** Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for Cleaning-Up:** Scoop up material and place in a disposal container.

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

- Handling:** Avoid contact with skin and eyes. Do not swallow. Avoid breathing vapour or mist. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking. (See section 8)
- General Hygiene Advice:** Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.



SAFETY DATA SHEET

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. (See section 10)

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Exposure Guidelines

Ingredient	Occupational Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Silica, crystalline, quartz	((10 mg/m ³)/(%SiO ₂ +2) TWA (resp)) ((30 mg/m ³)/(%SiO ₂ +2) TWA (total)) ((250)/(%SiO ₂ +5) mppcf TWA (resp))	0.025 mg/m ³
Asphalt	5 mg/m ³	0.5 mg/m ³ (fume)
Kaolin	15 mg/m ³	2 mg/m ³
Mica	20 mppcf	10 mg/m ³ (total); 3 mg/m ³ (resp)
Bentonite	Not available.	Not available.
Aluminatesilicate	Not available.	Not available.
Titanium dioxide	15 mg/m ³ (total dust)	10 mg/m ³
Acetaldehyde	200 ppm	Not available.
Ethyl acrylate	5 ppm	5 ppm

8.2 EXPOSURE CONTROLS

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTIVE MEASURES

Personal Protective Equipment:

Eye/Face Protection: Wear approved eye (properly fitted dust- or splash-proof chemical safety goggles) / face (face shield) protection.

Skin Protection:

Hand Protection: Wear suitable waterproof gloves.

Body Protection: Wear suitable waterproof protective clothing.

Respiratory Protection: A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

General Health and Safety Measures: Handle according to established industrial hygiene and safety practices. Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.



SAFETY DATA SHEET

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Paste.
Color:	Not available.
Odor:	Not available.
Odor Threshold:	Not available.
Physical State:	Paste.
pH:	Not available.
Melting Point/Freezing Point:	Not available.
Initial Boiling Point and Boiling Range:	Not available.
Flash Point:	Not available.
Evaporation Rate:	Not available.
Flammability:	Not Flammable.
Lower Flammability/Explosive Limit:	Not available.
Upper Flammability/Explosive Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Relative Density/Specific Gravity:	Not available.
Solubility:	Not available.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.
Viscosity:	Not available.
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	Not available.

Section 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2 CHEMICAL STABILITY

Stable under normal storage conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

10.4 CONDITIONS TO AVOID

Incompatible materials.



SAFETY DATA SHEET

10.5 INCOMPATIBLE MATERIALS

None known.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Likely Routes of Exposure: Skin contact, skin absorption, eye contact, inhalation, and ingestion.

Symptoms related to physical/chemical/toxicological characteristics:

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Skin: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause skin sensitization.

Ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

Acute Toxicity:

Ingredient	LC50	LD50
Silica, crystalline, quartz	Not available.	Oral 500 mg/kg, rat
Asphalt	Not available.	Oral >5000 mg/kg, rat Dermal >2000 mg/kg, rabbit
Kaolin	Not available.	Not available.
Mica	Not available.	Not available.
Bentonite	Not available.	Oral >5000 mg/kg, rat
Aluminatesilicate	Not available.	Not available.
Titanium dioxide	Not available.	Oral >10000 mg/kg, rat Dermal >10000mg/kg, rabbit
Acetaldehyde	Not available.	Oral 1930 mg/kg, rat
Ethyl acrylate	Inhalation 1414 ppm 4 h, rat	Oral 800 mg/kg, rat Dermal 500 µL/kg, rabbit

Calculated overall Chemical Acute Toxicity Values

LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
23.3 mg/L 4 h, rat	1122.4 mg/kg, rat	4026.5 mg/kg, rabbit

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Silica, crystalline, quartz	G-A2, I-1, N-1, O, CP65
Asphalt	G-A4, I-2B, N-1, O, CP65
Kaolin	G-A4
Mica	Not listed.
Bentonite	Not listed.
Aluminatesilicate	Not listed.
Titanium dioxide	G-A4, I-2B, O, CP65
Acetaldehyde	G-A3, I-1, I-2B, N-2, CP65
Ethyl acrylate	G-A4, I-2B, CP65



SAFETY DATA SHEET

11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation:	Based on available data, the classification criteria are not met.
Serious Eye Damage/Irritation:	Based on available data, the classification criteria are not met.
Respiratory Sensitization:	Based on available data, the classification criteria are not met.
Skin Sensitization:	May cause an allergic skin reaction.
STOT-Single Exposure:	Based on available data, the classification criteria are not met.
Chronic Health Effects:	
Carcinogenicity:	May cause cancer.
Germ Cell Mutagenicity:	This product is not classified as a mutagen.
Reproductive Toxicity:	
Developmental:	Based on available data, the classification criteria are not met.
Fertility:	Based on available data, the classification criteria are not met.
STOT-Repeated Exposure:	Causes damage to organs through prolonged or repeated exposure.
Aspiration Hazard:	Based on available data, the classification criteria are not met.
Toxicologically Synergistic Materials:	Not available.
Other Information:	Not available.

Section 12: ECOLOGICAL INFORMATION

12.1 ECOTOXICITY

Acute/Chronic Toxicity:	No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.
--------------------------------	--

12.2 PERSISTENCE AND DEGRADABILITY

Not available.

12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation:	Not available.
-------------------------	----------------

12.4 MOBILITY IN SOIL

Not available.

12.5 OTHER ADVERSE EFFECTS

Not available.

Section 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Disposal Method:	This material must be disposed of in accordance with all local, state, provincial, and federal regulations.
Other disposal recommendations:	Not available.



SAFETY DATA SHEET

Section 14: TRANSPORT INFORMATION

14.1 UN NUMBER

Not regulated.

14.2 UN PROPER SHIPPING NAME

Not applicable.

14.3 TRANSPORT HAZARD CLASS(ES)

Not applicable.

14.4 PACKING GROUP

Not applicable.

14.5 ENVIRONMENTAL HAZARDS

Not available.

14.6 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available.

14.7 SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Asphalt	Not listed.	Not listed.	Not listed.	Not listed.
Kaolin	Not listed.	Not listed.	Not listed.	Not listed.
Mica	Not listed.	Not listed.	Not listed.	Not listed.
Bentonite	Not listed.	Not listed.	Not listed.	Not listed.
Aluminatesilicate	Not listed.	Not listed.	Not listed.	Not listed.
Titanium dioxide	Not listed.	Not listed.	Not listed.	Not listed.
Acetaldehyde	Not listed.	Not listed.	1,000	313
Ethyl acrylate	Not listed.	Not listed.	1,000	313

State Regulations

California Proposition 65:

This product contains chemicals known to the State of California to cause cancer.



SAFETY DATA SHEET

Global Inventories:

Ingredient	USA TSCA
Silica, crystalline, quartz	Yes.
Asphalt	Yes.
Kaolin	Yes.
Mica	No.
Bentonite	Yes.
Aluminatesilicate	Yes.
Titanium dioxide	Yes.
Acetaldehyde	Yes.
Ethyl acrylate	Yes.

NFPA-National Fire Protection Association:

Health:	2
Fire:	1
Reactivity:	0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

- A1 - Confirmed human carcinogen.
- A2 - Suspected human carcinogen.
- A3 - Animal carcinogen.
- A4 - Not classifiable as a human carcinogen.
- A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

- 1 - The agent (mixture) is carcinogenic to humans.
- 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
- 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
- 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

- 1 - Known to be carcinogens.
- 2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Date of Preparation: March 15, 2013

Version: 1.0

Revision Date: July 17, 2014

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.



SAFETY DATA SHEET

Prepared by: Nexreg Compliance Inc.
Phone: (519) 488-5126
www.nexreg.com

Prepared for: Sakrete of North America

End of Safety Data Sheet