

## FEATURES & BENEFITS

### SAFETY

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit

### EYE/FACE WASH VALVE

Valve is designed so full continuous flow occurs with the simple squeeze of a lever providing an easy start to the irrigation process.

### HOSE


The 8' swivel hose delivers a wide coverage area and is pressure rated at 250 psi to further optimize durability.

### MOUNTING

Counter-mounted design provides a practical and space efficient piece of emergency equipment.

### EYE/FACE WASH

AXION MSR™ eye/face wash head (patent pending) uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.



## SPECIFICATIONS

Model 8904 counter-mounted eye/face wash and body spray shall include an AXION MSR™ eye/face wash head which features an inverted directional laminar flow which achieves zero vertical velocity supplied by an integral flow control. The unit shall also include a chrome plated brass stay-open squeeze lever valve, 8-foot 250 psi green hose with chrome-plated swivel fitting at one end, Noryl plastic deck flange with integral key slot for proper positioning of unit, universal sign, and 1/2" IPS inlet. In order to comply with state codes the use of a vacuum breaker is required with all hand held eye/face wash body spray units (Haws offers model SP212)

## APPLICATIONS

Perfect for the environment where safety is of the utmost importance and an extended coverage area may be needed. When installed properly, the functionally constructed, deck mounted design of the 8904 is space efficient.

Model 8904 is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.

## OPTIONS

- Vacuum Breaker: Model SP212 is a chrome-plated brass vacuum breaker.
- Repair Kit: Model VRKSP248 valve repair kit for Model SP248 squeeze handle valve.
- Alarm: Model 9001.5, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a 1/2" double pole, double throw flow switch.
- Tempered Water Blending Valves: Model 9201EFE; emergency valve thermostatically mixes hot and cold water to provide a safe fluid supply for emergency eyewash equipment, with a flow rate of 12 gpm.

To see all options for this model, visit [www.hawesco.com](http://www.hawesco.com)