

Catalog Number	
Notes	Type

FEATURES & SPECIFICATIONS

INTENDED USE

For use with housings LCP, L7XP, L7XPR, LC6, L7X, L7XR, L7XF and L7XFR.

CONSTRUCTION

Aluminum one-piece reflector.

White polyester powder coat paint.

All finishes are one-piece aluminum reflectors with integral flange.

Baffles available in black and white.

INSTALLATION

Socket to trim interface.

Trim retention is achieved by utilizing two side-mounted torsion springs on the trim and two receiving brackets in the can, ensuring a consistently tight fit with the ceiling.

LISTING



UL Listed to U.S. and Canadian safety standards.

Damp location listed.

6" Finishing Trim

CB1

BAFFLE SHALLOW
Wide Flange



Specifications

Height: 5-3/8 (13.7)

Lamp opening: 4-5/8 (11.7)

Diameter: 7-3/4 (19.7)

All dimensions are inches (centimeters).

ORDERING INFORMATION

For shortest lead times, configure product using **standard options** (shown in bold).

Example: **CB1 TOR**

CB1	
Series	Finish
CB1	(blank) White reflector with black baffle
	W White reflector with white baffle
	BN Brushed nickel reflector with black baffle ¹

TOR
Mounting method
TOR Torsion springs

NOTES:

¹ Flange matches trim finish.

Housing Compatibility

Housing and trim ordered separately.

Application	Source	Maximum wattage	Housing
IC	Incandescent	75 PAR30	LCP, LC6, L7X, L7XR, L7XP, L7XPR
		65 BR30	LCP, LC6, L7X, L7XR, L7XP, L7XPR
		40 A19	LCP, LC6, L7X, L7XR, L7XP, L7XPR
	Fluorescent	13 DTT	L7XF, L7XFR

CB1 6" Baffle Shallow Full Reflector Trim



Sheet #: CB1-TOR

©2009 Acuity Brands Lighting, Inc., 8/17/09

Lithonia Lighting
Recessed Downlighting
One Lithonia Way, Conyers, GA 30012
Phone: 800-315-4935 Fax: 770-918-1209
www.lithonia.com