

Version 2.1

Revision Date 02/09/2017

Print Date 05/09/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	A07698 ZEP COM S STL ZUSSTL14A 20N14 STK
Material number	:	0000000001046517
Manufacturer or supplier's c	leta	ils
Company	:	Zep Inc.
Address	:	1310 Seaboard Industrial Blvd., NW Atlanta, GA 30318
Telephone	:	404-352-1680

Emergency telephone numbers

For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Cleaner

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a compressed gas		
Colour	amber		
Odour	characteristic		

GHS Classification

Flammable aerosols Gases under pressure Skin irritation Eye irritation Skin sensitisation	 Category 1 Compressed gas Category 2 Category 2A Category 1
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.
Precautionary statements	: Prevention:



Version 2.1	Revision Date 02/09/2017	Print Date 05/09/2017
	P210 Keep away from heat/sparks	s/open flames/hot surfaces.
	P211 Do not spray on an open fla P251 Pressurized container: Do n	
	use. P261 Avoid breathing dust/ fume/ P264 Wash skin thoroughly after P272 Contaminated work clothing	handling.
	the workplace. P280 Wear eye protection/ face p P280 Wear protective gloves.	rotection.
	Response: P302 + P352 IF ON SKIN: Wash P305 + P351 + P338 IF IN EYES for several minutes. Remove cont easy to do. Continue rinsing.	Rinse cautiously with water
	P333 + P313 If skin irritation or ra advice/ attention.	sh occurs: Get medical
	P337 + P313 If eye irritation persi attention.	sts: Get medical advice/
	P362 Take off contaminated cloth Storage:	ing and wash before reuse.
	P410 + P412 Protect from sunlight temperatures exceeding 50 °C/ 12 Disposal:	•
	Dispose of contents/container in regulation.	accordance with local

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Concentration [%]
64742-52-5	>= 50 - < 70
64742-47-8	>= 10 - < 20
64742-89-8	>= 5 - < 10
5989-27-5	>= 1 - < 5
124-38-9	>= 1 - < 5
64742-96-7	>= 1 - < 5
67-63-0	>= 1 - < 5
5392-40-5	>= 0.1 - < 1
	64742-52-5 64742-47-8 64742-89-8 5989-27-5 124-38-9 64742-96-7 67-63-0

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
lf inhaled	 If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.



sion 2.1	Revision Date 02/09/2017	Print Date 05/09/201		
In case of skin contact				
In case of eye contact	: Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing If eye irritation persists, consult a Rinse immediately with plenty of v	specialist.		
If swallowed	 Keep respiratory tract clear. Never give anything by mouth to a If symptoms persist, call a physici DO NOT induce vomiting unless of physician or poison control center 	an. directed to do so by a		
Most important symptoms and effects, both acute and delayed	 Effects are immediate and delayer Symptoms may include irritation, in Effects are dependent on exposur contact time). Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction Review section 2 of SDS to see a 	redness, pain, and rash. re (dose, concentration, on.		
Notes to physician	: Treat symptomatically. Symptom	s may be delayed.		

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet	
Unsuitable extinguishing media	: High volume water jet	
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or war courses.	ter
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke	
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Further information	 Collect contaminated fire extinguishing water separately. The must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers. 	



Version 2.1 Revision Date 02/09/2017

Print Date 05/09/2017

Special protective equipment	:	Wear self-contained	breathing	apparatus	for firefighting if
for firefighters		necessary.			

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Always replace cap after use. Do not breathe vapours or spray mist.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Keep in a dry, cool and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Strong oxidizing agents



Version 2.1

Revision Date 02/09/2017

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible	Basis
			concentration	
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m3	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0
		PEL	5,000 ppm 9,000 mg/m3	CAL PEL
		STEL	30,000 ppm 54,000 mg/m3	CAL PEL
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
		PEL	400 ppm 980 mg/m3	CAL PEL
		STEL	500 ppm	CAL PEL



ersion 2.1		R	evision Da	ate 0	2/09/2017		Print Da	te 05/09	9/2017
	1					1,225 mg/m	13		1
citral		5392	-40-5		alable tion and	5 ppm		ACG⊩	1
Biological occupation	al expo	sure	limits						
Component	CAS-	No.	Contro paramet		Biological specimen		Permis concen		Basis
PROPAN-2-OL	67-63-	0	Acetone		Urine	End of shift at end of workwee k	40 mg/l		ACGIH BE
Personal protective ed Respiratory protection	luipme	: Us ve	ntilation is	s prov	ided or exp	nless adequa posure asses commended	sment de	emonst	rates
Hand protection									
Material Remarks		: Th		ty for	a specific v	workplace sh tective glove		discuss	ed
Eye protection		th	e workstat	ion le		s and safety	showers	are clo	ose to
		Tig	ghtly fitting	g safe	with pure wa ety goggles and protect	ater tive suit for a	abnormal	proces	sing

Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a compressed ga	S
Colour	: amber	
Odour	: characteristic	
Odour Threshold	: No data available	



Print Date 05/09/2017

A07698 ZEP COM S STL ZUSSTL14A 20N14 STK

Version 2.1	Revision Date 02/09/2017
рН	: Not applicable
Melting point/freezing point	: No data available
Boiling point	: 82.22 °C
Flash point	: No data available

Evaporation rate	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 0.856 g/cm3
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: not determined
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 44.04 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
leactions	Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon oxides

Version 2.1



Revision Date 02/09/2017

ZepInc

Print Date 05/09/2017

	Potential Health Effects		
	Aggravated Medical Condition Symptoms of Overexposure	 None known. Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration, contact time). 	
	Carcinogenicity:		
	IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed	
	OSHA	human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential	
	NTP	carcinogen by OSHA. No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.	
Αςι	ite toxicity		
	Product:		
	Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	
	Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	
	Components:		
	Distillates (petroleum), hydro Acute oral toxicity	otreated heavy naphthenic: : LD50 Rat: > 5,000 mg/kg	
	Acute inhalation toxicity	: LC50 Rat: > 5 mg/l Exposure time: 4 h	
	Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg	
	Distillates (petroleum), hydro Acute oral toxicity	otreated light: : LD50 Rat: > 5,000 mg/kg	
	Acute inhalation toxicity	: LC50 Rat: > 4.6 mg/l Exposure time: 6 h	
	Acute dermal toxicity	: LD50 Rat: > 2,000 mg/kg	
	(P) n months 1.8 dians:		

(R)-p-mentha-1,8-diene:



Version 2.1	Revision Date 02/09/2017	Print Date 05/09/2017
Acute oral toxicity	: LD50 Oral Rat: 4,400 mg/kg	
Acute dermal toxicity	: LD50 Dermal Rabbit: > 5,000 mg/kg	
propan-2-ol: Acute oral toxicity	: LD50 Oral Rat: 4,396 mg/kg Method: Calculation method	
Skin corrosion/irritation		
Product:		
Remarks: Irritating to skin.		
Serious eye damage/eye irritat	lion	
Product:		
Remarks: Irritating to eyes.		
Respiratory or skin sensitisatio	n	
Product:		
Remarks: Causes sensitisat	tion.	
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
Distillates (petroleum), hyd Distillates (petroleum), hyd Solvent naphtha (petroleum (R)-p-mentha-1,8-diene: carbon dioxide: Solvent naphtha (petroleum propan-2-ol: citral:	m), light aliph.:	
STOT - single exposure		
No data available		
STOT - repeated exposure		
No data available		
Aspiration toxicity		
No data available		
Further information		

Further information

Product:

SAFETY DATA SHEET



A07698 ZEP COM S STL ZUSSTL14A 20N14 STK

Version 2.1

Revision Date 02/09/2017

Print Date 05/09/2017

Remarks: No data available

Components:

Distillates (petroleum), hydrotreated light: Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available Bioaccumulative potential

Product:

<u>Product.</u>	
octanol/water <u>Components:</u> citral :	Remarks: No data available Pow: 2.76
Mobility in soil	
No data available	
Other adverse effects	
No data available <u> Product:</u>	
Regulation Remarks	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological : information	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.
<u>Components:</u> Distillates (petroleum), hydrotr	eated light :
Additional ecological : information	No data available



Version 2.1

Revision Date 02/09/2017

Print Date 05/09/2017

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule. No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.




Version 2.1	Revision Date 02/09/2017	Print Date 05/09/2017
SARA 311/312 Hazards	: Sudden Release of Pressure Hazard Acute Health Hazard Fire Hazard	
SARA 302	: No chemicals in this material are sub requirements of SARA Title III, Secti	, , ,
SARA 313	: This material does not contain any c known CAS numbers that exceed the reporting levels established by SARA	e threshold (De Minimis)
California Prop 65	This product does not contain any ch California to cause cancer, birth defe reproductive harm.	
The components of this	product are reported in the following inv	entories:
DSL	On TSCA Inventory This product contains the following componer Canadian DSL nor NDSL.	nts that are not on the
For information on the co	untry notification status for other regions plea	ase contact the

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION



OSHA - GHS Label Information:



.

Revision Date 02/09/2017

.

.

Print Date 05/09/2017

Version 2.1
Hazard piotogram

Hazard pictograms	
Signal w ord	: Danger:
Hazard statements	: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
Precautionary statements	:
	Prevention: Keep aw ay from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/ vapours/spray. Wash skin thoroughly after handling. Contaminated w ork clothing should not be allow ed out of the w orkplace. Wear eye protection/face protection. Wear protective gloves. Response : IF ON SKIN: Wash with plenty of soap and w ater. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and w ash before reuse. Storage : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.1
Revision Date:	02/09/2017
Print Date:	05/09/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.