



Issue date 16-Jul-2015

# Safety Data Sheet

Version 1

## 1. Identification of the Substance/Preparation and of the Company/Undertaking

### Product Identifier

**Product name** CHAMPION SPRAYON PREMIUM INTERIOR/EXTERIOR ENAMEL PINK  
**Chemical name** 6-5989-1

### Other means of identification

**Product code** FG 419-0901-2  
**Synonyms** Spray Paint

### Recommended use of the chemical and restrictions on use

**Recommended Use** Interior/exterior enamel.  
**Uses advised against** Do not use on surfaces that come in contact with food.

### Details of the supplier of the safety data sheet

| Supplier Address                                                               | Manufacturer Address                                                           |
|--------------------------------------------------------------------------------|--------------------------------------------------------------------------------|
| Chase Products Co.<br>2727 Gardner Road<br>Broadview, IL 60155<br>708-273-1121 | Chase Products Co.<br>2727 Gardner Road<br>Broadview, IL 60155<br>708-273-1121 |

### Emergency Telephone Number

**Company Phone Number** 708-865-1000  
**24 Hour Emergency Phone Number** 1-800-255-3924  
**Emergency telephone** ChemTel 1-800-255-3924

## 2. Hazards Identification

### Classification

|                                                    |               |
|----------------------------------------------------|---------------|
| Acute toxicity - Inhalation (Gases)                | Category 4    |
| Skin corrosion/irritation                          | Category 2    |
| Serious eye damage/eye irritation                  | Category 2    |
| Germ Cell Mutagenicity                             | Category 1B   |
| carcinogenicity                                    | Category 1B   |
| Reproductive Toxicity                              | Category 2    |
| Specific target organ toxicity (single exposure)   | Category 3    |
| Specific target organ toxicity (repeated exposure) | Category 2    |
| Aspiration toxicity                                | Category 1    |
| FLAMMABLE AEROSOLS                                 | Category 1    |
| Gases Under Pressure                               | liquefied gas |

### Label Elements

#### EMERGENCY OVERVIEW

**DANGER**

#### **hazard statements**

HARMFUL IF INHALED  
CAUSES SKIN IRRITATION  
Causes serious eye irritation  
May cause genetic defects  
May cause cancer  
Suspected of damaging fertility or the unborn child  
May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure  
 May be fatal if swallowed and enters airways  
**EXTREMELY FLAMMABLE AEROSOL**  
 Contains gas under pressure; may explode if heated



**Appearance** Pink liquid

**Physical State** Aerosol

**Odor** Characteristic odor of paint.

#### Precautionary Statements - Prevention

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Wear protective gloves, protective clothing, eye protection and face protection.  
 Use only outdoors or in a well-ventilated area  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not breathe fumes, mist, vapors or spray.  
 Keep away from heat, sparks, open flames and hot surfaces. — No smoking  
 Pressurized container: Do not pierce or burn, even after use  
 Do not spray on an open flame or other ignition source

#### Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention  
 Specific treatment: See additional cautionary statements on this label.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN: Wash with plenty of soap and water  
 If skin irritation occurs: Get medical advice/attention  
 Take off contaminated clothing and wash before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor if you feel unwell  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor  
 Do NOT induce vomiting

#### Precautionary Statements - Storage

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

##### Other Information

- Toxic to aquatic life with long lasting effects
  - Harmful to aquatic life
- 11.3282% of the mixture consists of ingredient(s) of unknown toxicity

### 3. Composition/information on Ingredients

**Synonyms** Spray Paint.  
**Chemical Family** MIXTURES.  
**Formula** 6-5989-1

| Chemical name | CAS No | weight-% | Trade secret |
|---------------|--------|----------|--------------|
|---------------|--------|----------|--------------|

|                                     |            |       |   |
|-------------------------------------|------------|-------|---|
| Acetone                             | 67-64-1    | 25-30 | * |
| Toluene                             | 108-88-3   | 15-20 | * |
| Propane                             | 74-98-6    | 15-20 | * |
| N-Butane                            | 106-97-8   | 10-15 | * |
| Light Aliphatic Naphtha             | 64742-49-0 | 1-5   | * |
| Titanium Dioxide                    | 13463-67-7 | 1-5   | * |
| Low Odor Mineral Spirits            | 64742-47-8 | <1    | * |
| Naphtha (petroleum), heavy aromatic | 64742-94-5 | <1    | * |

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First aid measures

### FIRST AID MEASURES

|                     |                                                                                                                                                                                                                                                             |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Eye Contact</b>  | Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.                               |
| <b>Skin contact</b> | Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.                                                                                                 |
| <b>inhalation</b>   | If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.     |
| <b>INGESTION</b>    | Call a poison control center or doctor for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person. |

### Most important symptoms and effects, both acute and delayed

|                 |                                                                                                                                                                                                                        |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Symptoms</b> | Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation. |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Indication of any immediate medical attention and special treatment needed

|                           |                                                                                                |
|---------------------------|------------------------------------------------------------------------------------------------|
| <b>Note to physicians</b> | Contains petroleum distillates, do not induce vomiting because of aspiration pneumonia hazard. |
|---------------------------|------------------------------------------------------------------------------------------------|

## 5. Fire-fighting measures

### Suitable extinguishing media

Dry chemical, CO2 or water spray.

**Unsuitable extinguishing media** Caution: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

**Hazardous combustion products** Thermal decomposition may yield gases like nitrogen oxides, carbon monoxide and carbon dioxide.

### Explosion data

**Sensitivity to Mechanical Impact** Contents under pressure. This product is extremely flammable. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Sensitivity to Static Discharge** Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

**For emergency responders** Remove all sources of ignition.

### Environmental Precautions

**Environmental Precautions** See Section 12 for additional Ecological Information.

### Methods and material for containment and cleaning up

**Methods for Containment** Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

**Methods for cleaning up** Clean contaminated surface thoroughly.

## 7. Handling and Storage

### Precautions for safe handling

**Advice on safe handling** Handle as an extremely flammable material. Avoid contact with skin, eyes and clothing. Store cans in a cool, dry place away from heat and open flame.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL III (NFPA-30B).**

**Incompatible Materials** Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

## 8. Exposure Controls/Personal Protection

### Control parameters

**Exposure guidelines** See occupational exposure limits listed below.

| Chemical name       | ACGIH TLV                     | OSHA PEL                                                                                                                                                                                                                                                                                                | NIOSH IDLH                                                   |
|---------------------|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| Acetone<br>67-64-1  | STEL: 750 ppm<br>TWA: 500 ppm | TWA: 1000 ppm<br>TWA: 2400 mg/m <sup>3</sup><br>(vacated) TWA: 750 ppm<br>(vacated) TWA: 1800 mg/m <sup>3</sup><br>(vacated) STEL: 2400 mg/m <sup>3</sup><br>The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors<br>(vacated) STEL: 1000 ppm | IDLH: 2500 ppm<br>TWA: 250 ppm<br>TWA: 590 mg/m <sup>3</sup> |
| Toluene<br>108-88-3 | TWA: 20 ppm                   | TWA: 200 ppm<br>(vacated) TWA: 100 ppm                                                                                                                                                                                                                                                                  | IDLH: 500 ppm<br>TWA: 100 ppm                                |

**FG 419-0901-2 CHAMPION SPRAYON PREMIUM INTERIOR/EXTERIOR ENAMEL PINK**

|                                           |                               |                                                                                                                                                                                  |                                                                                                             |
|-------------------------------------------|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
|                                           |                               | (vacated) TWA: 375 mg/m <sup>3</sup><br>(vacated) STEL: 150 ppm<br>(vacated) STEL: 560 mg/m <sup>3</sup><br>Ceiling: 300 ppm                                                     | TWA: 375 mg/m <sup>3</sup><br>STEL: 150 ppm<br>STEL: 560 mg/m <sup>3</sup>                                  |
| Propane<br>74-98-6                        | TWA: 1000 ppm                 | TWA: 1000 ppm<br>TWA: 1800 mg/m <sup>3</sup><br>(vacated) TWA: 1000 ppm<br>(vacated) TWA: 1800 mg/m <sup>3</sup>                                                                 | IDLH: 2100 ppm<br>TWA: 1000 ppm<br>TWA: 1800 mg/m <sup>3</sup>                                              |
| N-Butane<br>106-97-8                      | STEL: 1000 ppm                | (vacated) TWA: 800 ppm<br>(vacated) TWA: 1900 mg/m <sup>3</sup>                                                                                                                  | TWA: 800 ppm<br>TWA: 1900 mg/m <sup>3</sup>                                                                 |
| Titanium Dioxide<br>13463-67-7            | TWA: 10 mg/m <sup>3</sup>     | TWA: 15 mg/m <sup>3</sup> total dust<br>(vacated) TWA: 10 mg/m <sup>3</sup> total dust                                                                                           | IDLH: 5000 mg/m <sup>3</sup>                                                                                |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 | STEL: 150 ppm<br>TWA: 100 ppm | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>(vacated) TWA: 100 ppm<br>(vacated) TWA: 435 mg/m <sup>3</sup><br>(vacated) STEL: 150 ppm<br>(vacated) STEL: 655 mg/m <sup>3</sup> | -                                                                                                           |
| Pigment Red 52.2<br>12238-31-2            | -                             | (vacated) Ceiling: 5 mg/m <sup>3</sup><br>Ceiling: 5 mg/m <sup>3</sup> Mn                                                                                                        | IDLH: 500 mg/m <sup>3</sup> Mn<br>TWA: 1 mg/m <sup>3</sup> Mn<br>STEL: 3 mg/m <sup>3</sup> Mn               |
| Ethylbenzene<br>100-41-4                  | TWA: 20 ppm                   | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>(vacated) TWA: 100 ppm<br>(vacated) TWA: 435 mg/m <sup>3</sup><br>(vacated) STEL: 125 ppm<br>(vacated) STEL: 545 mg/m <sup>3</sup> | IDLH: 800 ppm<br>TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>STEL: 125 ppm<br>STEL: 545 mg/m <sup>3</sup> |

**Appropriate engineering controls**
**Engineering controls**

Use with adequate general or local exhaust ventilation.

**Individual protection measures, such as personal protective equipment**
**Eye/face Protection**

Conventional eyeglasses to guard against splashing.

**Skin and Body Protection**

Chemical resistant gloves required.

**Respiratory protection**

Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

**General hygiene considerations**

Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

**9. Physical and Chemical Properties**
**Information on basic physical and chemical properties**

|                              |                                                                         |                          |                               |
|------------------------------|-------------------------------------------------------------------------|--------------------------|-------------------------------|
| <b>Physical State</b>        | Aerosol                                                                 | <b>Odor</b>              | Characteristic odor of paint. |
| <b>Appearance</b>            | Pink liquid                                                             | <b>Odor threshold</b>    | No information available      |
| <b>Color</b>                 | Pink                                                                    |                          |                               |
| <b>Property</b>              | <b>Values</b>                                                           | <b>Remarks • Method</b>  |                               |
| pH                           | Not applicable                                                          | Solvent-based product.   |                               |
| Melting point/freezing point | Not applicable                                                          | No information available |                               |
| Boiling point/boiling range  | Acetone 133 F/56.29 C                                                   | No information available |                               |
| Flash Point                  | Not available. This is an aerosol product with a Flame Projection of 18 | No information available |                               |

|                                     |                                                                             |                          |
|-------------------------------------|-----------------------------------------------------------------------------|--------------------------|
|                                     | in. with 3 in. flashback. Temperatures above 120 F may cause cans to burst. |                          |
| <b>Evaporation Rate</b>             | Faster than butyl acetate                                                   | No information available |
| <b>Flammability (solid, gas)</b>    |                                                                             | No information available |
| <b>Flammability Limits in Air</b>   |                                                                             | No information available |
| <b>Upper flammability limits</b>    | Not available                                                               |                          |
| <b>Lower Flammability Limit</b>     | Not available                                                               |                          |
| <b>Vapor pressure</b>               |                                                                             | No information available |
| <b>Vapor Density</b>                |                                                                             | No information available |
| <b>Relative Density</b>             | 0.882 concentrate                                                           | No information available |
| <b>Water solubility</b>             | Insoluble in water                                                          | No information available |
| <b>Solubility in other solvents</b> |                                                                             | No information available |
| <b>Partition coefficient</b>        |                                                                             | No information available |
| <b>Autoignition Temperature</b>     |                                                                             | No information available |
| <b>Decomposition temperature</b>    |                                                                             | No information available |
| <b>Kinematic viscosity</b>          |                                                                             | No information available |
| <b>Dynamic viscosity</b>            |                                                                             | No information available |
| <b>Explosive properties</b>         | No information available                                                    |                          |
| <b>Oxidizing properties</b>         | No information available                                                    |                          |

#### Other Information

|                         |                          |
|-------------------------|--------------------------|
| <b>Softening point</b>  | No information available |
| <b>Molecular weight</b> | No information available |
| <b>VOC content (%)</b>  | 55.53%                   |
| <b>Density</b>          | 7.35 lb/gal concentrate  |
| <b>Bulk Density</b>     | No information available |

### 10. Stability and Reactivity

#### Reactivity

Not applicable                      no data available

#### Chemical stability

Stable.

#### Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

**hazardous polymerization**                      Hazardous polymerization does not occur.

#### Conditions to Avoid

Temperatures above 122 °F (50 °C).

#### Incompatible Materials

Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

#### Hazardous decomposition products

Thermal decomposition may yield gases like nitrogen oxides, carbon monoxide and carbon dioxide.

### 11. Toxicological Information

#### Information on likely routes of exposure

|                            |                                                                                      |  |  |
|----------------------------|--------------------------------------------------------------------------------------|--|--|
| <b>Product Information</b> | This product has not been tested as whole. See below for information on ingredients. |  |  |
| <b>inhalation</b>          | no data available.                                                                   |  |  |
| <b>Eye Contact</b>         | no data available.                                                                   |  |  |
| <b>Skin contact</b>        | no data available.                                                                   |  |  |
| <b>INGESTION</b>           | no data available.                                                                   |  |  |

| Chemical name | Oral LD50 | dermal LD50 | Inhalation LC50 |
|---------------|-----------|-------------|-----------------|
|---------------|-----------|-------------|-----------------|

## FG 419-0901-2 CHAMPION SPRAYON PREMIUM INTERIOR/EXTERIOR ENAMEL PINK

|                                                      |                       |                          |                                       |
|------------------------------------------------------|-----------------------|--------------------------|---------------------------------------|
| Acetone<br>67-64-1                                   | = 5800 mg/kg ( Rat )  | -                        | = 50100 mg/m <sup>3</sup> ( Rat ) 8 h |
| Toluene<br>108-88-3                                  | = 2600 mg/kg ( Rat )  | = 12000 mg/kg ( Rabbit ) | = 12.5 mg/L ( Rat ) 4 h               |
| Propane<br>74-98-6                                   | -                     | -                        | = 658 mg/L ( Rat ) 4 h                |
| N-Butane<br>106-97-8                                 | -                     | -                        | = 658 g/m <sup>3</sup> ( Rat ) 4 h    |
| Light Aliphatic Naphtha<br>64742-49-0                | > 5000 mg/kg ( Rat )  | > 3160 mg/kg ( Rabbit )  | = 73680 ppm ( Rat ) 4 h               |
| Titanium Dioxide<br>13463-67-7                       | > 10000 mg/kg ( Rat ) | -                        | -                                     |
| Low Odor Mineral Spirits<br>64742-47-8               | > 5000 mg/kg ( Rat )  | > 2000 mg/kg ( Rabbit )  | > 5.2 mg/L ( Rat ) 4 h                |
| Naphtha (petroleum), heavy<br>aromatic<br>64742-94-5 | > 5000 mg/kg ( Rat )  | > 2 mL/kg ( Rabbit )     | > 590 mg/m <sup>3</sup> ( Rat ) 4 h   |

### Information on toxicological effects

**Symptoms** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** May cause skin irritation and reddening after prolonged or repeated contact with skin.  
**Serious eye damage/eye irritation** Irritating to eyes.  
**irritation** May cause skin and eye irritation.  
**corrosivity** Not applicable.  
**sensitization** No information available.  
**Germ Cell Mutagenicity** See Section 2 of this SDS.  
**carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical name                  | ACGIH | IARC     | NTP | OSHA |
|--------------------------------|-------|----------|-----|------|
| Toluene<br>108-88-3            |       | Group 3  |     |      |
| Titanium Dioxide<br>13463-67-7 |       | Group 2B |     | X    |

**Reproductive Toxicity** See Section 2 of this SDS.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Aspiration Hazard** No information available.

### Numerical measures of toxicity - Product Information

**Unknown acute toxicity** 11.3282% of the mixture consists of ingredient(s) of unknown toxicity  
**The following values are calculated based on chapter 3.1 of the GHS document .**  
**ATEmix (oral)** 21118 mg/kg  
**ATEmix (dermal)** 31293 mg/kg  
**ATEmix (inhalation-gas)** 15680 mg/l  
**ATEmix (inhalation-dust/mist)** 15.9 mg/l  
**ATEmix (inhalation-vapor)** 840 mg/l

## 12. Ecological Information

This product contains chemicals which are listed as a marine pollutants according to DOT.

### ecotoxicity

48.8287% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Chemical name | Algae/aquatic plants | Fish | Toxicity to<br>Microorganisms | Crustacea |
|---------------|----------------------|------|-------------------------------|-----------|
|---------------|----------------------|------|-------------------------------|-----------|

|                                                      |                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                          |                                                                                                         |
|------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|---------------------------------------------------------------------------------------------------------|
| Acetone<br>67-64-1                                   |                                                                                                                                   | 6210 - 8120: 96 h<br>Pimephales promelas mg/L<br>LC50 static 4.74 - 6.33: 96 h<br>Oncorhynchus mykiss mL/L<br>LC50 8300: 96 h Lepomis<br>macrochirus mg/L LC50                                                                                                                                                                                                                                                                                                                                                                                                  | EC50 = 14500 mg/L 15 min | 10294 - 17704: 48 h<br>Daphnia magna mg/L EC50<br>Static 12600 - 12700: 48 h<br>Daphnia magna mg/L EC50 |
| Toluene<br>108-88-3                                  | 433: 96 h<br>Pseudokirchneriella<br>subcapitata mg/L EC50<br>12.5: 72 h<br>Pseudokirchneriella<br>subcapitata mg/L EC50<br>static | 15.22 - 19.05: 96 h<br>Pimephales promelas mg/L<br>LC50 flow-through 12.6: 96 h<br>Pimephales promelas mg/L<br>LC50 static 5.89 - 7.81: 96 h<br>Oncorhynchus mykiss mg/L<br>LC50 flow-through 54: 96 h<br>Oryzias latipes mg/L LC50<br>static 11.0 - 15.0: 96 h<br>Lepomis macrochirus mg/L<br>LC50 static 28.2: 96 h<br>Poecilia reticulata mg/L<br>LC50 semi-static 50.87 -<br>70.34: 96 h Poecilia<br>reticulata mg/L LC50 static<br>14.1 - 17.16: 96 h<br>Oncorhynchus mykiss mg/L<br>LC50 static 5.8: 96 h<br>Oncorhynchus mykiss mg/L<br>LC50 semi-static | EC50 = 19.7 mg/L 30 min  | 5.46 - 9.83: 48 h Daphnia<br>magna mg/L EC50 Static<br>11.5: 48 h Daphnia magna<br>mg/L EC50            |
| Light Aliphatic Naphtha<br>64742-49-0                |                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                          | 2.6: 96 h Chaetogammarus<br>marinus mg/L LC50                                                           |
| Low Odor Mineral Spirits<br>64742-47-8               |                                                                                                                                   | 45: 96 h Pimephales<br>promelas mg/L LC50<br>flow-through 2.4: 96 h<br>Oncorhynchus mykiss mg/L<br>LC50 static 2.2: 96 h<br>Lepomis macrochirus mg/L<br>LC50 static                                                                                                                                                                                                                                                                                                                                                                                             |                          | 4720: 96 h Den-dronereides<br>heteropoda mg/L LC50                                                      |
| Naphtha (petroleum), heavy<br>aromatic<br>64742-94-5 | 2.5: 72 h Skeletonema<br>costatum mg/L EC50                                                                                       | 41: 96 h Pimephales<br>promelas mg/L LC50 1740:<br>96 h Lepomis macrochirus<br>mg/L LC50 static 2.34: 96 h<br>Oncorhynchus mykiss mg/L<br>LC50 45: 96 h Pimephales<br>promelas mg/L LC50<br>flow-through 19: 96 h<br>Pimephales promelas mg/L<br>LC50 static                                                                                                                                                                                                                                                                                                    |                          | 0.95: 48 h Daphnia magna<br>mg/L EC50                                                                   |

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

| Chemical name                                     | Partition coefficient |
|---------------------------------------------------|-----------------------|
| Acetone<br>67-64-1                                | -0.24                 |
| Toluene<br>108-88-3                               | 2.65                  |
| Propane<br>74-98-6                                | 2.3                   |
| N-Butane<br>106-97-8                              | 2.89                  |
| Naphtha (petroleum), heavy aromatic<br>64742-94-5 | 2.9 - 6.1             |

**Other adverse effects**

No information available

**13. Disposal Considerations**

**FG 419-0901-2 CHAMPION SPRAYON PREMIUM INTERIOR/EXTERIOR ENAMEL PINK****Waste treatment methods****Disposal of wastes**

Dispose of in accordance with federal, state and local regulations.

**Contaminated packaging**

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

| Chemical name       | RCRA | RCRA - Basis for Listing                                                                 | RCRA - D Series Wastes | RCRA - U Series Wastes |
|---------------------|------|------------------------------------------------------------------------------------------|------------------------|------------------------|
| Acetone<br>67-64-1  |      | Included in waste stream:<br>F039                                                        |                        | U002                   |
| Toluene<br>108-88-3 | U220 | Included in waste streams:<br>F005, F024, F025, F039,<br>K015, K036, K037, K149,<br>K151 |                        | U220                   |

| Chemical name       | RCRA - Halogenated Organic Compounds | RCRA - P Series Wastes | RCRA - F Series Wastes                                                                                                                                                                                                                                                                                                                                                                                                                                                       | RCRA - K Series Wastes |
|---------------------|--------------------------------------|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| Toluene<br>108-88-3 |                                      |                        | Toxic waste<br>waste number F025<br>Waste description:<br>Condensed light ends, spent<br>filters and filter aids, and<br>spent desiccant wastes from<br>the production of certain<br>chlorinated aliphatic<br>hydrocarbons, by free<br>radical catalyzed processes.<br>These chlorinated aliphatic<br>hydrocarbons are those<br>having carbon chain lengths<br>ranging from one to and<br>including five, with varying<br>amounts and positions of<br>chlorine substitution. |                        |

| Chemical name       | California Hazardous Waste Status |
|---------------------|-----------------------------------|
| Acetone<br>67-64-1  | Ignitable                         |
| Toluene<br>108-88-3 | Toxic<br>Ignitable                |

**14. Transport Information****DOT**

UN/ID no

Proper Shipping Name

Hazard Class

Marine pollutant

Limited Quantity - Spray Paint

UN1950

Limited quantity (LQ)

2.1

This product contains chemicals which are listed as a marine pollutants according to DOT.

**15. Regulatory information****International Inventories**

TSCA

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

DSL

All ingredients are listed or are excluded from listing on the DSL.

## FG 419-0901-2 CHAMPION SPRAYON PREMIUM INTERIOR/EXTERIOR ENAMEL PINK

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

### US Federal Regulations

#### SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

| Chemical name      | CAS No   | weight-% | SARA 313 - Threshold Values % |
|--------------------|----------|----------|-------------------------------|
| Toluene - 108-88-3 | 108-88-3 | 15-20    | 1.0                           |

#### SARA 311/312 Hazard Categories

|                                   |     |
|-----------------------------------|-----|
| Acute Health Hazard               | yes |
| Chronic Health Hazard             | yes |
| Fire Hazard                       | yes |
| Sudden release of pressure hazard | No  |
| Reactive Hazard                   | No  |

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical name       | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Toluene<br>108-88-3 | 1000 lb                     | X                      | X                         | X                          |

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical name       | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ)                   |
|---------------------|--------------------------|----------------|--------------------------------------------|
| Acetone<br>67-64-1  | 5000 lb                  |                | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ |
| Toluene<br>108-88-3 | 1 lb                     |                | RQ 1 lb final RQ<br>RQ 0.454 kg final RQ   |

### US State Regulations

#### California Proposition 65

This products contains < 0.01% ethyl benzene and <0.01% naphthalene, chemicals known to the State of California to cause cancer. This product contains the following Proposition 65 chemicals.

| Chemical name                 | California Proposition 65            |
|-------------------------------|--------------------------------------|
| Toluene - 108-88-3            | Developmental<br>Female Reproductive |
| Titanium Dioxide - 13463-67-7 | Carcinogen                           |

#### U.S. State Right-to-Know Regulations

| Chemical name                  | New Jersey | Massachusetts | Pennsylvania |
|--------------------------------|------------|---------------|--------------|
| Acetone<br>67-64-1             | X          | X             | X            |
| Toluene<br>108-88-3            | X          | X             | X            |
| Propane<br>74-98-6             | X          | X             | X            |
| N-Butane<br>106-97-8           | X          | X             | X            |
| Titanium Dioxide<br>13463-67-7 | X          | X             | X            |

#### U.S. EPA Label information

EPA Pesticide registration number Not applicable

|                              |
|------------------------------|
| <b>16. Other information</b> |
|------------------------------|

|             |                   |                |                    |                                                 |
|-------------|-------------------|----------------|--------------------|-------------------------------------------------|
| <u>NFPA</u> | Health Hazards 2  | Flammability 4 | Instability 1      | Physical and chemical properties Not applicable |
| <u>HMIS</u> | Health Hazards 2* | Flammability 4 | Physical Hazards 1 | Personal Protection B                           |

Prepared by Regulatory Department  
 Issue date 16-Jul-2015

Revision note  
 This SDS supersedes a previous MSDS dated May 20, 2009.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet