

SAFETY DATA SHEET
BOARDWALK DUST MOP TREATMENT 20N18

Version 2.3

Revision Date 12/22/2016

BWK352A

Print Date 03/21/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : Boardwalk Dust Mop Treatment BWK352A

Material number : 1041289 / A06412

Manufacturer or supplier's details

Company : Boardwalk / Essendant Co.

Address : One Parkway North
Deerfield, IL 60015

Telephone : 844-828-5617

Emergency telephone numbers

For SDS Information : 844-828-5617

For a Medical Emergency :

**For a Transportation
Emergency** : Chemtel: 1(800)255-3924

Recommended use of the chemical and restrictions on use

Recommended use : Floor Care

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	white
Odour	characteristic

GHS Classification

Gases under pressure : Liquefied gas

Skin irritation : Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P332 + P313 If skin irritation occurs: Get medical advice/
attention.

SAFETY DATA SHEET

BOARDWALK DUST MOP TREATMENT 20N18

Version 2.3

Revision Date 12/22/2016

BWK352A

Print Date 03/21/2017

P362 Take off contaminated clothing and wash before reuse.

Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	$\geq 10 - < 20$
Distillates (petroleum), hydrotreated light	64742-47-8	$\geq 5 - < 10$
Solvent naphtha (petroleum), heavy aliph.	64742-96-7	$\geq 5 - < 10$
butane	106-97-8	$\geq 5 - < 10$
Naphtha (petroleum), hydrotreated light	64742-49-0	$\geq 5 - < 10$
propane	74-98-6	$\geq 1 - < 5$

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
Move out of dangerous area.
- If inhaled : If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
Wash off immediately with plenty of water for at least 15 minutes.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
Rinse immediately with plenty of water for at least 15 minutes.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Keep respiratory tract clear.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Causes skin irritation.
Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray jet
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Sweep up or vacuum up spillage and collect in suitable container for disposal.
-

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
-

SAFETY DATA SHEET
BOARDWALK DUST MOP TREATMENT 20N18

BWK352A

Version 2.3

Revision Date 12/22/2016

Print Date 03/21/2017

Take precautionary measures against static discharges.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Open drum carefully as content may be under pressure.
 Always replace cap after use.
 Dispose of rinse water in accordance with local and national regulations.
 Do not breathe vapours or spray mist.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
 No smoking.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.
 Keep in a dry, cool and well-ventilated place.

Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm	OSHA P0

SAFETY DATA SHEET
BOARDWALK DUST MOP TREATMENT 20N18

BWK352A

Version 2.3

Revision Date 12/22/2016

Print Date 03/21/2017

			1,800 mg/m3	
		PEL	1,000 ppm	CAL PEL
			1,800 mg/m3	

Engineering measures : none

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Safety glasses
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : white

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point : No data available

Flash point :
Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : The product is not flammable.

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.93 g/cm3

Solubility(ies)

SAFETY DATA SHEET
BOARDWALK DUST MOP TREATMENT 20N18

BWK352A

Version 2.3

Revision Date 12/22/2016

Print Date 03/21/2017

Water solubility	: emulsifiable
Solubility in other solvents	: not determined
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash.

Carcinogenicity:

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SAFETY DATA SHEET
BOARDWALK DUST MOP TREATMENT 20N18

Version 2.3

Revision Date 12/22/2016

BWK352A

Print Date 03/21/2017

Acute toxicity

Product:

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l
Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l
Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

butane:

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l
Exposure time: 2 h

LC50 Rat: 1,355 mg/l

propane:

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l
Exposure time: 2 h

LC50 Rat: 658 mg/l
Exposure time: 4 h

LC50 Rat: 1,355 mg/l

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: May irritate eyes.

Respiratory or skin sensitisation

SAFETY DATA SHEET
BOARDWALK DUST MOP TREATMENT 20N18

Version 2.3

Revision Date 12/22/2016

BWK352A

Print Date 03/21/2017

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Distillates (petroleum), hydrotreated heavy naphthenic:

Distillates (petroleum), hydrotreated light:

**Solvent naphtha (petroleum), heavy aliph.:
butane:**

Naphtha (petroleum), hydrotreated light:

propane:

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

Components:

Distillates (petroleum), hydrotreated light:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n- : Remarks: No data available
octanol/water

Components:

butane :

Partition coefficient: n- : Pow: 2.89
octanol/water

SAFETY DATA SHEET
BOARDWALK DUST MOP TREATMENT 20N18

BWK352A

Version 2.3

Revision Date 12/22/2016

Print Date 03/21/2017

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

Components:

Distillates (petroleum), hydrotreated light :

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):
UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air):
UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air):
UN1950, AEROSOLS, 2.2, - Limited quantity

SAFETY DATA SHEET
BOARDWALK DUST MOP TREATMENT 20N18

BWK352A

Version 2.3

Revision Date 12/22/2016

Print Date 03/21/2017

Transportation Regulation: TDG (Canada):
UN1950, AEROSOLS, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.
No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Sudden Release of Pressure Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

ethylbenzene 100-41-4
benzene 71-43-2
naphthalene 91-20-3

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

toluene 108-88-3
benzene 71-43-2

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory
DSL All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

SAFETY DATA SHEET BOARDWALK DUST MOP TREATMENT 20N18

Version 2.3

Revision Date 12/22/2016

BWK352A

Print Date 03/21/2017


Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	2

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA GHS Label Information:

Hazard pictograms



Signal word

: **Warning:**

Hazard statements

: Contains gas under pressure; may explode if heated. Causes skin irritation.

Precautionary statements

:

Prevention: Wash skin thoroughly after handling. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

Storage: Protect from sunlight. Store in a well-ventilated place.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.3
Revision Date:	12/22/2016
Print Date:	03/21/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.