

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Back Bars

Underbar Equipment Back Bars

Model: TBB-2SG/SB





= FEATURES & BENEFITS =

■ Efficient refrigeration system

Turbo Air's refrigerators are designed with oversized and balanced R-134A (CFC Free) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

- Forced air cooling system
- Fast cooling and balanced temperature throughout the cabinet.
- Stainless steel countertop and interior
 The exterior of cabinet is constructed with heavy gauge reinforced stainless steel countertop and wear-resistant black vinyl coated galvanized steel. Interior is stainless steel except galvanized steel top. Turbo Air Back Bar model guarantees utmost in cleanliness and long product life. It also can add a touch of style to the most refined setting.
- LED lighting interior display system
 Brighter and longer lasting LED lights provide attractive, enhanced illumination compared to fluorescents. It saves energy by producing
- Triple pane thermal glass (SG Models)
 Triple pane thermal glass provides extra ability to maintain cool temperatures.

■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

■ Side mount compressor unit

By positioning the compressor on the side of the unit, refrigerators can now be serviced without being moved. Our innovative, front breathing feature also allows this model to provide high efficiency in narrow spaces.

 Refrigerator holds 33°F ~ 38°F for the best in beverage preservation











ENERGY STAR® Qualified

‡ ENERGY STAR rated models

less heat.

Model	Swing Door	CU./FT.	1/2 Barrels	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
TBB-2SG TBB-2SB‡	2 2	19 19	2 2	6	1/3 1/4	7 7	344 332	583/4 x 271/4 x 371/8 583/4 x 271/4 x 371/8

(unit: inch)

Model: TBB-2SG/2SB

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type				
Full Load Amperes	7			
Compressor HP	1/3(SG) / 1/4(SB)			
Refrigerant	R-134A			
Cord Length (ft.)	9			
Lamp (W)	30			
DIMENSIONAL DATA				
1/2 Barrels	2			
Cubic Feet	19			
Ext. Length Overall in.	58 _{3/4} (1492mm)			
Ext. Depth Overall in.*	27 _{1/4} (692mm)			
Ext. Height Overall in.†	37 _{1/8} (945mm)			
Net Weight lbs	276(SG) / 286(SB)			
Gross Weight lbs	344(SG) / 332(SB)			
# of Swing Door	2			
# of Shelves	6			
Shelf size (LxD) in.	(R)20 x 193/8, (L)243/8 x 193/8			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


- Self-contained system
- 4" swivel casters standard
- 2" casters available (optional)
- 6" adjustable legs available (optional)
- Door locks standard (SB model only)

OPTIONAL ACCESSORIES :


- ☐ 2.5" Diameter casters
- □ 5" Diameter casters
- ☐ 6" ABS plastic legs
- □ Additional PE coated wire shelves


PLAN VIEW





PLAN VIEW





Ver.201504











ENERGY STAR® Qualified

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002









^{*}Depth does not include 1" for door handle (SG Models).
Depth does not include 2" for rear spacers.

[†] Height does not include 5" for caster height.