

Class 1 Div 2 LED Pivoting Light - 2 foot 3 lamp - Offshore LED Rig Light Fixture

Part #: HAL-24-3L-LED-BMSW

**Made in the USA**

The Larson Electronics HAL-24-3L-LED-BMSW Hazardous Area LED Light Fixture is U.S./Canada U.L. approved Class 1 Division 2 Groups A, B, C and D - UL 1598A listed, has a T4A temperature rating, and ideal for hazardous locations where flammable chemical/petrochemical vapors may be occasionally encountered.

The HAL-24-3L-LED-BMSW fixture is a 2 foot long, 3 lamp, UL listed Class 1 Division 2 Groups A, B, C and D hazardous area LED light that takes the reliability and efficiency of a fluorescent fixture and adds even longer lamp life and efficiency with high output LEDs. This fixture is T4A temperature rated and comes standard with our high power 15 watt LED lamps. The lamps are protected by a powder coated aluminum frame and shatter and heat resistant clear acrylic lens secured with four zinc coated steel draw latches.

The fixture is constructed of copper free aluminum alloy and powder coated. The lamp reflector is corrosion resistant heavy gauge aluminum and coated with a high gloss reflective finish. This fixture can be configured to run on 120 to 277VAC as well as 12-24VDC and is U.L. 595 and UL 1598A Marine Type approved for use in marine environments. The HAL-24-3L-LED-BMSW is weatherproof and provides operators in hazardous locations with a highly efficient, reliable and affordable lighting solution for open areas where flammable chemicals and vapors may occasionally be present.

We have eliminated the ballast normally associated with fluorescent fixtures which reduces overall weight, increases lamp life to an extreme 50,000 hours and helps this LED fixture maintain a T4A temperature rating. The solid state design of the included LED lamps give this fixture superior resistance to damage from vibrations and extremes in temperature as well as a lamp service life over twice that of standard T8 bulbs. The 15 watt LED lamps produce more illumination than standard T8 bulbs, but draw only 3/4 of the current. The current generation of Larson Electronics LED T-series style bulbs produce 15% more light than standard T8 bulbs. This fixture is multi-voltage capable (not multi-tap) and works on the following voltages: 120 Volt 60 HZ, 220 Volt 50 HZ, 240 Volt 60 HZ, 277 Volts 60 HZ. We also make a 12-24V DC version for low voltage applications (-LV suffix). Our HAL-24-3L-LED-BMSW LED light fixture is both U.S. and Canada U.L. approved.

Standard Surface Mount Brackets: Each L bracket is cinched to the bracket mounting peg on each side of the light. The angle of the bracket is set by tightening two bolts on either side of the bracket. The bolts act as a set screw. The bracket itself is mounted via a single bolt hole at the top the bracket. There are two brackets. Once the brackets are mounted to a surface (ceiling, floor or wall), the light fixture can be pivoted by loosening the that hold the bracket to the mounting peg. This fixture allows 45 degrees of pivot from the 90 degree point.

Suggested Applications: Aircraft maintenance, Oil drilling rigs, Refineries, Solvent and cleaning areas, Gas processing plants, Chemical manufacturing, Waste treatment plants, Gas processing plants.

Made in USA Quality

1. Each unit dialectically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost. Adjustable mounting brackets enable the operator to choose any mounting angle for the fixture, where other models may only offer one or three choices.
3. Fixture constructed streamlined ribbed corrosion-resistant, copper free extruded aluminum body for better heat dissipation and extended ballast life.
4. Aluminum extruded lens frame for greater strength
5. Relamping done via 10 draw latches, which enable the operator to unlatch the lens and access the lamps.
5. Heavy gauge extruded aluminum reflectors with high gloss reflective finish. Resists dents and corrosion.
6. 3/4 inch, threaded access hole for wiring conduit.
7. Units can be wired end to end in series.

Superior LED Benefits

1. 50,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off – No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.

Specifications / Additional Information**HAL-24-3L-LED-BMSW Hazardous Area****UL Listing:** United States - Canada**Dimensions:** W-7" L-25 1/2" H-6 1/8"**Weight:** 14 Lbs**Total Watts:** 45 watts**Voltage:** Multi- 120V-60hz 220V-50hz 240V-60hz 277V-60hz**Low Voltage (Optional):** 12-24V DC**LED Lamp Life Expectancy:** 50,000 Hours**Efficiency:** 90 Lumens per Watt**Operating Temp Range: T4A rated** -30 C to 85 C**Beam Angle:** 150 degrees**Color Temp:** 5300K- Color Rendering Index-75**Mounting:** Back Mount Swivel Bracket**Wiring Hub:** 3/4 inch threaded**Warranty:** YES- 5 Years***Minimum Operating Temp:** -30 C**Maximum Case Temp:** 90 C**U.L Approval:** [U.S Certificate](#) [Canada Certificate](#)

*5 year warranty replacement on this LED light (or LED bulbs for light fixtures with removable LED bulbs). After 30 days, the customer ships the failed LED light and/or LED bulb to Larson Electronics at their expense. If the failure is a manufacturer defect, we will ship a new replacement to the customer. If failure occurs within 30 days of receipt, Larson Electronics will provide a return label via email to the customer. When the failed light is returned, we will ship a new replacement.

Scroll Down to Purchase- Please note: 2 day lead time on this light.

Part #: [HAL-24-3L-LED-BMSW \(70078\)](#)

U.L. Ratings

Class 1 Division 2, Groups A, B, C, D

UL 595 Outdoor Marine Type (Saltwater)

UL 1598A Marine Type

California Title 24 Compliant

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671**Intl:** 1-903-498-3363**E-mail:** sales@larsonelectronics.com





Links (Click on the below items to view):

[- Dimensional Drawing](#)

[- STEP](#)