

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product identifier used on the label:

Product Name: Coated Abrasive GHS Template

 $\underline{\hbox{Other means of identification:}}$

Recommended use of the chemical and restrictions on use:

Product Use/Restriction:

Abrasive Product.

 $\underline{\hbox{Chemical manufacturer address and telephone number:}}\\$

Manufacturer Name: Saint-Gobain Abrasives, Inc.
Address: 1 New Bond Street

Worcester, MA 01615 www.Nortonabrasives.com

General Phone Number: 508-795-5000

Emergency phone number:

Website:

Emergency Phone Number: 508-795-5000

SECTION 2: HAZARD(S) IDENTIFICATION

 $\underline{\textit{Classification of the chemical in accordance with CFR 1910.1200(d)(f):}\\$

Signal Word: Not applicable.

GHS Class: Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Hazard Statements: Not applicable.

Precautionary Statements: Not applicable.

Hazards not otherwise classified that have been identified during the classification process:

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Eye: Causes eye irritation.

Skin: Causes skin irritation.

 ${\bf Inhalation:} \qquad \qquad {\bf Prolonged \ or \ excessive \ inhalation \ may \ cause \ respiratory \ tract \ irritation.}$

Ingestion: May be harmful if swallowed. May cause vomiting.

Chronic Health Effects: Prolonged or repeated contact may cause skin irritation.

Signs/Symptoms: Overexposure may cause headaches and dizziness.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing None generally recognized. Conditions:

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

| Chemical Name | CAS# | Ingredient Percent | EC Num. |
|----------------------------------|------------|--------------------|-----------|
| | | | |
| Epoxy resin | 25068-38-6 | 1 - 5 by weight | |
| Lithium stearate | 4485-12-5 | 1 - 5 by weight | 224-772-5 |
| Titanium dioxide | 13463-67-7 | 0 - 1 by weight | 236-675-5 |
| Talc, Magnesium silicate hydrate | 14807-96-6 | 1 - 5 by weight | 238-877-9 |
| Nylon | No Data | 30 - 60 by weight | |
| Melamine Resin | 9003-08-1 | 1 - 5 by weight | |
| Polyurethane resin | 67700-43-0 | 10 - 30 by weight | |

10 - 30 by weight 215-691-6 1344-28-1 Aluminum Oxide, Non-fibrous

SECTION 4: FIRST AID MEASURES

Description of necessary measures:

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue Eye Contact:

rinsing. Get medical attention, if irritation or symptoms of overexposure persists.

Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists. Skin Contact:

If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention. Inhalation:

If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give Ingestion:

anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed:

Other First Aid: Not applicable.

Indication of immediate medical attention and special treatment needed:

Note to Physicians: Not applicable.

SECTION 5: FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires Suitable Extinguishing Media:

involving this material.

Not applicable. Unsuitable extinguishing media:

Specific hazards arising from the chemical:

Hazardous Combustion Not applicable.

Not applicable. Unusual Fire Hazards:

Special protective equipment and precautions for fire-fighters:

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent)

and full protective gear.

Not applicable. Fire Fighting Instructions:

NFPA Ratings:

NFPA Health: 1 NFPA Flammability: 1

NFPA Reactivity: 0



SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use

proper personal protective equipment as listed in Section 8

Environmental precautions:

Spill Cleanup Measures:

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Not applicable.

Methods and materials for containment and cleaning up:

Methods and materials for containment and cleaning up:

Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by Methods for containment:

covering, diking or other means. Provide ventilation.

Clean up spills immediately observing precautions in the protective equipment section. Place into a suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water Methods for cleanup:

to remove trace residue.

Reference to other sections:

SECTION 7: HANDLING and STORAGE

Precautions for safe handling:

Handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

Conditions for safe storage, including any incompatibilities:

Storage: Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and

incompatible substances. Keep container tightly closed when not in use.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

| Ingredient | Guideline OSHA | Guideline A CGIH | Quebec Canada | Ontario Canada | Alberta Canada |
|-------------------------------------|---|---|---|--|--|
| Titanium dioxide | | TLV-TWA: 10 mg/m3 | VEMP-TWA: 10 mg/m3 Total particulate/dust (T) | OEL-TWAEV: 10 mg/m3 Total particulate/dust (T) | OEL-TWA: 10 mg/m3 Total particulate/dust (T) |
| Talc, Magnesium silicate hydrate | PEL-TWA: 20 mppcf | TLV-TWA: 2 mg/m3 Respirable fraction (R) TLV-TWA: 1 mg/m3 Respirable fraction (R) | VEMP-TWA: 3 mg/m3 Respirable fraction (R) | OEL-TWAEV: 2 f/cc Respirable fraction (R) | OEL-TWA: 2 mg/m3 Respirable fraction (R) |
| Aluminum Oxide, Non- fibrous | PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T) | TLV-TWA: 10 mg/m3 | VEMP-TWA: 10 mg/m3 Total particulate/dust (T) | OEL-TWAEV: 10 mg/m3 Total particulate/dust (T) | OEL-TWA: 10 mg/m3 |
| Ingredient | Mexico | British Columbia Canada | | | |
| Titanium dioxide | MPE-PPT: 0.1 mg/m3 Respirable fraction (R) | OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-TWA: 3 mg/m3 Respirable fraction (R) | | | |
| Talc, Magnesium silicate hydrate | LMPE-PPT: 2 mg/m3 Respirable fraction (R) | OEL-TWA: 2 mg/m3 Respirable fraction (R) | | | |
| Aluminum Oxide, Non- fibrous | MPE-PPT: 0.1 mg/m3 Respirable fraction (R) | OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-STEL: 20 mg/m3 Total particulate/dust (T) | | | |

Appropriate engineering controls:

Engineering Controls:

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance

of the personal protective equipment.

Individual protection measures:

PPE Pictograms:

Meltina Point:

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166. Eye/Face Protection:

Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be Skin Protection Description:

used to prevent contact with eyes, skin or clothing.

Respiratory Protection:

A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety



Not determined.

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:

Physical State Appearance: Solid article. Color: Not determined. Odor: Odorless. Odor Threshold: Not determined. Boiling Point: Not determined.

Density: Not determined. Solubility: Not determined. Vapor Density: Not determined. Vapor Pressure: Not determined. Evaporation Rate: Not determined. Not determined. Viscosity: Not determined. Not determined.

Coefficient of Water/Oil Distribution:

Flammability:

Not determined.

Flash Point: None.

Lower Flammable/Explosive Limit: Not applicable. Upper Flammable/Explosive Limit: Not applicable. Auto Ignition Temperature: Not applicable.

Explosive Properties: Excessive dust accumulation could present a potential combustible dust hazard.

VOC Content: Not determined.

SECTION 10: STABILITY and REACTIVITY

Reactivity:

Reactivity: Not applicable.

Chemical Stability:

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization: Not reported.

Conditions To Avoid:

Conditions to Avoid: Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.

Incompatible Materials:

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

<u>Hazardous Decomposition Products:</u>

Special Decomposition Products: Not applicable.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

Acute Toxicity: This product has not been tested for its toxicity.

| Carcinogens: | | | | | | | |
|-----------------------------|-------------------|---------|---------|---------|---------|--|-------------------|
| | ACGIH | NIOSH | OSHA | IARC | NTP | | MEXICO |
| Aluminum Oxide, Non-fibrous | | No Data | No Data | No Data | No Data | | A4 Not |
| | Classifiable as a | | | | | | Classifiable as a |
| | Human | | | | | | Human |
| | Carcinogen | | | | | | Carcinogen |

Epoxy resin:

RTECS Number: SL6475000

Eye - Rabbit Standard Draize test.: 100 mg [mild] (RTECS)

Ingestion:

Oral - Rat LD50 : 11400 mg/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Nutritional and Gross Metabolic - Weight loss or decreased weight gain]
Oral - Mouse LD50 : 15600 mg/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Nutritional and Gross Metabolic - Weight loss or decreased weight gain] (RTECS)

Lithium stearate :

RTECS Number: WI4370000

Oral - Rat LD50: 15 gm/kg [Behavioral - Somnolence (general depressed activity) Behavioral -Ingestion:

Changes in motor activity (specific assay) Skin and Appendages - Hair] (RTECS)

<u>Titanium dioxide</u>:

RTECS Number: XR2275000

Skin - Human Standard Draize test. : 300 ug/3D-I - [mild] (RTECS) Skin:

Inhalation - Rat TCLo - Lowest published toxic concentration: 1 mg/kg - [Lungs, Thorax, or Respiration - Other changes Biochemical - Metabolism (Intermediary) - Effect on inflammation or mediation of inflammation] (RTECS) Inhalation:

Oral - Rodent rat TDLo - Lowest published toxic dose: 60 gm/kg - [Gastrointestinal - Hypermotility, diarrhea Gastrointestinal - Other changes] (RTECS) Ingestion:

Talc, Magnesium silicate hydrate:

RTECS Number: WW2710000

Aluminum Oxide, Non-fibrous:

RTECS Number: BD1200000

Inhalation:

Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema;

Related to Chronic Data - death] (RTECS)

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: Please contact the phone number or address of the manufacturer listed in Section 1 for information on

ecotoxicity.

SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste:

Waste Disposal:

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

guidelines.

SECTION 14: TRANSPORT INFORMATION

UN number: Not regulated as hazardous material for transportation. UN proper shipping name: Not regulated as hazardous material for transportation. Transport hazard class(es): Not regulated as hazardous material for transportation. Packing group: Not regulated as hazardous material for transportation. Environmental hazards: Not regulated as hazardous material for transportation.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

Inventory Status

Special precautions for user:

| | Japan ENCS | South Korea KECL | Australia AICS | Canada DSL | TSCA Inventory |
|----------------------------------|------------|------------------|----------------|------------|----------------|
| | | | | | Status |
| Epoxy resin | | | | Listed | Listed |
| Lithium stearate | | | | Listed | Listed |
| Titanium dioxide | | | | Listed | Listed |
| Talc, Magnesium silicate hydrate | | | | Listed | Listed |
| Aluminum Oxide, Non-fibrous | (1) -23 | KE-01012 | Listed | Listed | Listed |

Not regulated as hazardous material for transportation.

Aluminum Oxide, Non-fibrous:

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

<u>Lithium stearate</u>:

EC Number: 224-772-5

<u>Titanium dioxide</u>:

EC Number: 236-675-5

Talc, Magnesium silicate hydrate:

EC Number: 238-877-9

Aluminum Oxide, Non-fibrous:

FC Number: 215-691-6

State Right To Know

| | RI | MN | IL | PA | МА |
|----------------------------------|----|----|----|--------|--------|
| Titanium dioxide | | | | Listed | Listed |
| Talc. Magnesium silicate hydrate | | | | Listed | Listed |

| | 1 | | | | |
|-----------------------------|---|--------|---------|--------|--------|
| Aluminum Oxide, Non-fibrous | Listed | Listed | No Data | Listed | Listed |
| | | | | | |
| | NJ | | | | |
| Titanium dioxide | No Data | | | | |
| Aluminum Oxide, Non-fibrous | Listed: NJ Hazardous List; Substance Number: 2891 | | | | |

SECTION 16: ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 1
HMIS Fire Hazard: 1
HMIS Reactivity: 0



SDS Creation Date: August 15, 2009
SDS Revision Date: March 31, 2015
SDS Revision Notes: GHS Update

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.