



# Coldform2™ single lamination Oil only pads

1CFWPSL



Coldform2™ | Oil only | Pads | Single lamination

**Basis weight:** Heavy

**Absorbency:** 24 US Gallons | 91 Liters of oil\*\*

**Base Fiber:** Cellulose




## Coldform2™

Product Code	Color	Weight	Format	Size inches (cm)	Recycled Content	Units/Case	LTL/Pallet	FTL/Pallet
Oil only								
1CFWPSL	White	Heavy	Pads	16" x 18" (40 cm x 46 cm)	80%*	100	30	36

## Single lamination Coldform2™

Spun-bond cover  
Coldform™ core



This product is in an Oil only format



This is one of our heavy weight products



Pad size is 16" x 18" (40 cm x 46 cm)



This product is always in stock



80% recycled content

There are 100 heavy weight pads in the bale which represent a heavier per square foot absorbent product.

This Oil only Coldform2™ pad is unique in the fact that one side is no-lint and very durable, and the other side is soft and absorbent. It combines some of the best features found in a laminated pad (non-linting & durability) while reducing the slip problem associated with double sided laminated sorbents. This pad is more absorbent than its meltblown counterpart. These features make this pad a great Coldform2™ go-to Oil only product.

Each pad is 16" x 18" (40 cm x 46 cm) and features perforations 8" in-line. The pads are supplied in a clear plastic bag.

### Key features

- Best option for absorbing oil-based liquids
- The sorbent is made up of two layers that are sonically welded together.
- Made from 80% recycled/sustainable cellulose

\* Basis weights and recycled content are ± 5%

\*\* Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

- Top layer is made of a white, no-lint, durable spun-bond polypropylene.
- Core/base layer is made from high loft Coldform2™ sustainable fibers.
- Base layer is low-slip making this a great product for foot traffic.
- Pads are perforated down their center for more economical use.

### Application

Because the top sheet is very durable and the bottom layer is low-slip, this product makes a very good sorbent choice if foot traffic is expected, or when durability is needed. This Oil only product can be used indoors or outdoors but it is not recommended for use where large amounts of water are present.

### Notes

- Fire retardant as per ASTM 726.
- Ensure that disposal of these sorbents complies with all state and federal regulations.

## Compliance

Related Regulations	Description
29CFR 1910.22(a)(2)	"The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition."
29CFR 1910.120(j)(1)(vii)	"... suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur."