

# CHECKERBOARD TAPE

## PRODUCT INFORMATION GUIDE

<b>Application(s):</b>	Laminated checkerboard tape is an excellent product to bring visual attention to hazards in the workplace. The tape is constructed using a sub-surface printing method to ensure longevity. The base material is a high performance biaxially oriented polypropylene film with a gloss clear polyester over lamination. Adhesive will adhere to most any clean, dry surface.
<b>Adhesive:</b>	Acrylic Emulsion
<b>Face Stock:</b>	3.50 MIL white polypropylene with 1.0 MIL polyester over lamination
<b>Total Thickness:</b>	4.90 MIL
<b>Surface Application:</b>	Minimum application temperature 8 <sup>0</sup> C (45 <sup>0</sup> F) Operational temperature -53 <sup>0</sup> C (-65 <sup>0</sup> F) to 93 <sup>0</sup> C (200 <sup>0</sup> F) Surface must be clean, dry, smooth and free from dust, dirt, grease and oils.
<b>Shelf Life:</b>	One year from date of purchase when stored at 70 <sup>0</sup> F, 50% relative humidity.
<b>Safety Note:</b>	Laminated tape products have a smooth slick surface that will become particularly slippery when wet. Please take this into consideration when choosing this product for your intended application.

Property:	Test Method:	Measurement:
<b>Adhesive</b> Coat Weight Shear Quick Tack 90 Degree Peel	(Hours)	38 lb/MSF or 11.4 lbs/3,000 sqft 11 hours 26 oz/sqin (min) 2 min. Dwell-Room Temp.

**INCOM**  
MANUFACTURING GROUP  
www.incomdirect.com

This data is based on typical results achieved. It is the sole responsibility of the buyer or user to ensure that the product is suitable for any proposed end use or application and to ensure proper cleaning of the substrate to which it will be applied. This data in no way constitutes a specification, nor should it be seen as a recommendation for use. We accept no liability for any loss, damage or injury resulting from the use of these products or data.

February 2009.