

HAZARD TAPE - CONFORMABLE

PRODUCT INFORMATION GUIDE

Application(s):	Our conformable hazard warning tape products are an economical way to bring visual identification to safety related issues and hazards. The base color of the tape is throughout the vinyl with the striped pattern printed on with a durable process. Tape is conformable to most any surface, and will adhere to most clean dry surfaces.
Adhesive:	Crosslinked Rubber Adhesive
Carrier:	Vinyl (6 MIL)
Total Thickness:	6.8 MIL
Specifications:	Meets Federal Specification: PPP-T-66E
Liner:	No Liner - Tape Is Self Wound
Shelf Life:	One year from date of purchase when stored at 70 ⁰ F, 50% relative humidity.

Property:	Test Method:	Measurement:
PVC Film		
Thickness	PSTC-33	6 mils
Tensile Strength	ASTM-D638	> 15 lb / inch
Elongation	ASTM-D638	> 150%
Rubber Adhesive		
Dry Coat Weight	PSTC-33	35 g/m ² (0.066 oz/yd ²)
180 Peel Adhesion	PSTC-1	> 1 lb / inch
Operational Temp.		(-10 to 60 ⁰ C) -14 to 140 ⁰ F
Min Application Temp.		10 ⁰ C (50 ⁰ F)