# ChemZoil NL-339

# **DESCRIPTION AND GENERAL PROPERTIES**

## Material Neoprene

- Length (inches) 14
- Thickness (inches) 0.050 (Heavy Wt.)
- Colour/Color Black
- Interior finish Textile support
- Exterior finish Pebbled
- Size / EAN 8 9 10 11
- Packaging 6 pairs/carton



# **PERFORMANCE RESULTS**

# Certification category 3

ABCJKL







X1XXXX

3121



For more details: www.mapa-pro.com



# ChemZoil NL-339

# **DESCRIPTION AND GENERAL PROPERTIES**

- Superior chemical resistance against acids and alkalis, such as concentrated hydrofluoric acid, oils, and greases, due to its 100% neoprene multi-layer construction
- Pebbled embossing, for better grip on wet and slippery objects
- Excellent mechanical resistance and longer service life, due to the textile support and the thickness of the glove
- Thermal insulation from the cotton-knit lining for handling hot liquids

# **MAIN FIELDS OF USE**

### Chemical industry

- Handling and transporting drums of chemical products
- · Handling on alkylation units
- Resin and adhesive manufacturing
- Site pollution control
- Hot, petrochemical product sampling

# **INSTRUCTIONS FOR USE**

### Instructions for use

- •It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- •Persons sensitized to dithiocarbamates should not use these gloves.
- •Inspect the gloves for any defect before use.
- •Put the gloves on dry, clean hands.
- •Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www. mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- •Turn the cuff end down in order to prevent a hazardous chemical from dipping onto the arm.
- •Inspect the gloves for cracks or snags before reusing them.

#### Storage conditions

Store the gloves in their original packaging at a temperature not below 5°C.

### Laundering conditions

Before taking off the gloves, clean them as appropriate :

- •in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
- •in use with a solvent ( diluents, etc): rub over with a dry cloth
- •in use with acids and alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth

Caution : improper use of the gloves or submitting them to another cleaning or laundering process which is not specifically recommended can alter their performance levels.

#### **Drying conditions**

Ensure the inside of the gloves is dry before reusing them.

### Food contact US

FDA 21CFR 177.2600

### LEGISLATION

This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council. This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH). • CE-Type Examination Certificate

0072/014/162/10/01/0144 • Issued by the notified body nr 0072 I.F.T.H. – Av. Guy de Collongue - F-69134 ECULLY CEDEX



# Mechanical industry

• Surface treatment of metals (acids)